

RS Stainless

Random Sidedrive Carton Sealer

The BestPack™ RS Stainless Steel Series is a Semi-Automatic Random Tape Carton Sealer built for speed and rugged dependability. Using side belt drives, the RS-S easily seals a wide range of random carton weights and sizes, with masts that allow for an extra 4" of carton height on the upper assembly. Able to effectively seal very light to very heavy cartons, BestPack's RS Stainless Steel Series sealers are used where there are wet environments. Units are available for either splash resistant or wash-down applications.

All BestPack stainless steel units are crafted with food grade 304 stainless steel for 21 CFR 110 compliance and our RS line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment.



Key Points of the Carton Sealer



Operator Fed



Random Cartons



Top & Bottom Seal

Features

- Heavy Duty 2mm Food Grade 304 Stainless Steel Welded Frame Including Upper Welded Legs
- Random Side Belt Drive System with 1-piece Molded Belts and V-belt Guide
- Accepts 2" and 3" Pop-out BestPack High Speed Food Grade 304 Stainless Steel Tape Heads
- Electrical On/Off Box is Mounted on the Left Side
- Uses Heavy Duty SMC Oil-less Cushioned Air-cylinders
- Adjustable Bed Height 20.5" to 30.0"
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Upper Random Mast is Tapped and Drilled that can be Raised (Un-bolted, Raised and Re-bolted) for an Extra 4" Carton Height if Needed
- Quality UL Approved Electrical Parts

Options

- Food Grade 304 Stainless Steel Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Food Grade 304 Stainless Steel Heavy Duty Dual Locking Casters
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Aluminum Frame Interlock Safety Gates

Extra Accessories to Improve Efficiency



Spare Parts Kit May Vary

Spare Parts Kit



Food Grade 304 Stainless Steel Locking Casters



Food Grade 304 Stainless Steel Long Infeed/Exit Conveyor w/ L-Bracket



Food Grade 304 Stainless Steel Spare High Speed Tape Head

- High Speed Motor Upgrade (Up to 125 ft.)
- Food Grade 304 Stainless Steel Short Infeed/Exit Conveyor w/L-Bracket
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 15 Cartons/min.
Speed

80 PSI
5 SCFM
Air Requirements

432-632 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
RS 22-2S 2" Tape Head	(42.9") x (34.8") x (71.8")	(6.0" - U) x (4.25" - 20.0") x (4.0" - 21.0")	(20.5" - 30.0")	Up to 15	432
RS 22-3S 3" Tape Head	(42.9") x (34.8") x (71.8")	(6.0" - U) x (5.25" - 21.0") x (4.0" - 21.0")	(20.5" - 30.0")	Up to 15	432
RS 23-2S 2" Tape Head	(42.9") x (34.8") x (76.0")	(6.0" - U) x (4.5" - 21.6") x (4.0" - 30.0")	(20.5" - 30.0")	Up to 12	464
RS 23-3S 3" Tape Head	(42.9") x (34.8") x (76.0")	(6.0" - U) x (5.5" - 21.6") x (4.0" - 30.0")	(20.5" - 30.0")	Up to 12	464
RS 32-2S 2" Tape Head	(42.9") x (44.2") x (71.8")	(6.0" - U) x (4.5" - 30.0") x (4.0" - 21.0")	(20.5" - 30.0")	Up to 12	487
RS 32-3S 3" Tape Head	(42.9") x (44.2") x (71.8")	(6.0" - U) x (5.5" - 30.0") x (4.0" - 21.0")	(20.5" - 30.0")	Up to 12	487
RS 33-3S 3" Tape Head	(42.9") x (44.2") x (76.0")	(6.0" - U) x (5.5" - 30.0") x (4.0" - 30.0")	(20.5" - 30.0")	Up to 12	632

Information subject to change without notice.

U - Unlimited
All Models available in High Speed & Food Grade 304 Stainless Steel