

## RSBFT Series

### Random Sidedrive Bottom Flap Folder

The BestPack RSBFT Series is a random operator-fed, bottom carton sealer designed to reduce the time required to fold & seal the bottom flaps of a carton. This unit can be used when random size carton forming volume has become too large to manually form and tape the cartons, but the volume is too small to justify a fully automatic carton erector/sealer.



Our RSBFT line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.

## Key Points of the Carton Sealer



Operator Fed



Random Cartons



Bottom Seal

### Features

- Handles Random Carton Sizes
- Two Side Belts
- Bottom Seal Only
- Random Bottom Flap Folder
- "T" Rail with Bottom Major Flap Folding Horns
- The Unit Reduces Operator Fatigue and Increases Output.
- Compared to Hand Taping, the Quality of the Seal and the Appearance of the Carton is Greatly Improved.
- Adjustable Bed Height from 23.5" to 30.0"
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads

- Exclusive Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm
- Maintenance Free Oil-less Air Cylinders
- High Speed Motors
- Operation Manual

### Options

- Food Grade 304 Stainless Steel
- Spare Parts Kit
- Exit Conveyors
- Locking Casters w/ Support Brackets

# Extra Accessories to Improve Efficiency



\*Spare Parts Kit May Vary\*

Spare Parts Kit



Locking Casters  
w/Support Brackets



Long Exit Conveyor



Spare Tape Head

- Carton Sealing Tape

## Machine & Carton Specifications

**110 Volts 60 Hz**  
Power Requirements

**Up to 10 Cartons/min.**  
Speed

**60-80 PSI**  
5 SCFM (Dry Air)  
Air Requirements

**350 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
RSBFT20-2H** <b>2" Tape Head</b>	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30.0")	Up to 10	350
RSBFT20-3H** <b>3" Tape Head</b>	(95.9") x (35.5") x (29.4")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0+)"	(23.5" - 30.0")	Up to 10	350

Information subject to change without notice.

\* Outside Dimensions Only  
\*\* High Speed