

RSL

Random Sidedrive Low Profile Carton Sealer

The BestPack™ RSL Series is a Semi-Automatic Random Tape Carton Sealers designed to seal very low profile cartons in addition to the wide range expected of a random carton sealer. Build for speed and durability, the RSL's low profile feature allows for the effective sealing of cartons at a minimum height of 2.5". The RSL is capable of sealing cartons up to 20.5" tall as well.

Our RSL line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Random Cartons



Top & Bottom Seal

Features

- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Random Side Belt Drive System with 1-piece Molded Belts and V-belt Guide
- Seals Cartons as Low as 2.5" in Height
- Available with 2" and 3" BestPack High speed Tape Heads
- Electrical On/Off Box can also be Easily Mounted on Either Side of the Sealer (Left Side is Standard)
- Uses Heavy Duty SMC Oil-less Cushioned Air-cylinders
- Upper Random Mast is Tapped and Drilled that can be Raised (Un-bolted, Raised and Re-bolted) for an Extra 4" Carton Height if Needed
- Quality UL Approved Electrical Parts

- Adjustable Bed Height from 20.5" to 30.0"
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.

Options

- Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

Extra Accessories to Improve Efficiency



Carton Sealing Tape



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket Stabilizer



Spare Parts Kit May Vary

Spare Parts Kit

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Short Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 12 Cartons/min.
Speed

55-60 PSI
5 SCFM
Air Requirements

450 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
RSL 22-2 2" Tape Head	(60.4") x (34.8") x (71.8")	(6.0" - U) x (5.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30.0")	Up to 12	450
RSL 22-3 3" Tape Head	(60.4") x (34.8") x (71.8")	(6.0" - U) x (6.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30.0")	Up to 12	450

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
All Models available in High Speed & Food Grade 304 Stainless Steel