

MTD Series

Manual Top & Bottom Drive Dual Mast Sealer

The BestPack™ MTD Series is a Semi-Automatic Adjustable Tape Carton Sealer, engineered for the economical and effective operator-fed closure of difficult to seal cartons. The MTD Series is four belt drive, to accommodate tall unstable cartons, and comes standard with a manual self-centering mechanism that permits the operator to quickly center the carton and the tape. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly.

Our MTD line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

Features

- Telescopic Dual Mast Design
- Designed for Uniform Applications
- 4 Belt Drive - 2 Top and 2 Bottom Belts
- Adjustable Bed Height: MTD22 - 23.5" - 30"
MTD33 - 25.8" - 30"
- Extra 4" Height Adjustment Available on Upper Assembly
- Height Adjustment on Either Side of Machine
- Upper Side Compression Unit
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Guide Rail Centering Mechanism
- 3" Model Capable of Interchanging 2" or 3" Tape Heads

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft.)
- Motorized Height Adjustment
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Interlock Safety Gates
- Low Tape or No Tape Sensor
- Food Grade 304 Stainless Steel

Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Food Grade 304 Stainless Steel
- Short Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 40 Cartons/min.
Speed

None
Air Requirements

345 - 375 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.***	Shipping Weight (lbs.)
MTD22-2 2" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (6.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 40	345
MTD22-2H** 2" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (6.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 50	345
MTD22-3 3" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (7.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 40	345
MTD22-3H** 3" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (7.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 50	345
MTD33-3 3" Tape Head	(35.3") x (43.8") x (79.7")	(6.0" - U) x (7.5" - 30.0") x (4.0" - 30.0")	(25.8" - 30.0")	Up to 40	375
MTD33-3H** 3" Tape Head	(35.3") x (43.8") x (79.7")	(6.0" - U) x (7.5" - 30.0") x (4.0" - 30.0")	(25.8" - 30.0")	Up to 50	375

Information subject to change without notice.

* Outside Dimensions Only
** High Speed
*** Based on a 12" long carton
U - Unlimited