

RS Bottom Only

Random Bottom Only Sealer

The BestPack™ RS20 Series is a Semi-Automatic Random Bottom Carton Sealer designed to fulfill light to heavy duty random bottom sealing needs. This unit is incredibly effective when random bottom carton sealing volume has become too large for hand sealing.

Our RS20 line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Random Cartons



Bottom Seal

Features

- Handles Random Carton Sizes
- Side Belt Drive
- Adjustable Bed Height from 20.5" - 30"
- Exclusive Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Maintenance Free Oil-less Cylinders
- Heavy Duty Frame
- UL Approved Electrical Parts
- Electrical On/Off Box can be Mounted on Either Side of the Carton Sealer
- Tool Kit & Operation Manual

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Interlock Safety Gates
- Low Tape or No Tape Sensor
- Food Grade 304 Stainless Steel

Extra Accessories to Improve Efficiency



Spare Parts Kit May Vary

Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Short Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 15 Cartons/min.
Speed

80 PSI
5 SCFM
Air Requirements

330-380 lbs
Shipping Weight

| Model | Machine Dimensions Length x Width x Height | Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.) | Conveyor Height Adjustment Height (min. - max.) | Cartons per min. | Shipping Weight (lbs.) |
|-------------------------------|---|--|--|---------------------|---------------------------|
| RS20-2 2" Tape Head | (42.9") x (30.0") x (28.8") | (6.0" - U) x (4.25" - 20.0") x (4.0+)" | (20.5" - 30.0") | Up to 15 | 318 |
| RS20-3 3" Tape Head | (42.9") x (30.0") x (28.8") | (6.0" - U) x (5.25" - 21.0") x (4.0+)" | (20.5" - 30.0") | Up to 15 | 318 |
| RS30-2 2" Tape Head | (42.9") x (39.4") x (28.8") | (6.0" - U) x (4.5" - 30.0") x (4.0+)" | (20.5" - 30.0") | Up to 15 | 380 |
| RS30-3 3" Tape Head | (42.9") x (39.4") x (28.8") | (6.0" - U) x (5.5" - 30.0") x (4.0+)" | (20.5" - 30.0") | Up to 15 | 380 |

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
All Models available in High Speed & Food Grade 304 Stainless Steel