

BG16

1.6 mil (40 micron) total tape thickness
22 micron cast BOPP low elongation film
Rohm & Haas Acrylic Adhesive

BestPackTM
the total tape sealing solution

Overview:

BG16 is specially formulated for 100% recycled corrugated. By adding better quick tack properties to the benefits of acrylic, BG Tape is a perfect alternative to Hot Melt Tape.

About Our Product:

- Good Initial Quick Tack
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temp.
- Does not yellow due to UV exposure (Sunlight & Fluorescent Lighting)
- Unlimited Shelf Life
- Available in Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance
- RoHS Compliant
- Tape Manufactured in ISO 9001 & 14001 Facilities



Product Specifications:

| | | |
|------------------------|--------------------------------|---------------------|
| Adhesive Type: | Rohm & Haas Acrylic | Test Method: |
| Total Thickness: | 1.6 mil (40 micron) | ASTM D-3652 |
| Film Thickness: | 0.9 mil (22 micron) | ASTM D-3652 |
| Adhesive Thickness: | 0.7 mil (18 micron) | ASTM D-3652 |
| Tensile Strength: | 15 lbs/inch width | ASTM D-3759 |
| Peel Adhesion: | 16 oz/inch width | ASTM D-3330 |
| Elongation % at Break: | 110% | ASTM D-3759 |

Service Temperature:

Min. Service Temp.: **-30°F**
Max. Service Temp.: **200°F**

Usage & Storage Temperature:

Min. Usage & Storage Temp.: **32°F**
Max. Usage & Storage Temp.: **150°F**

Ideal Storage Temperature:

Ideal Storage Temp.: **77°F +/- 5°F**
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.

Available Colors:



Available Lengths:

| |
|--------------|
| 100m |
| 914m |
| 1372m |

Available Widths:

| |
|-------------|
| 48mm |
| 72mm |