



CSEG FULLY AUTOMATIC RANDOM SIDEDRIVE

The BestPack[™] CSEG Series is a Fully Automatic Random Carton Sealer. Designed for flexibility and high speed, our advanced engineering allows the CSEG to seal cartons and crate pass through at 27 cartons per minute. Our CSEG machine is purpose built for the egg industry's standard carton sizes: 30, 24, 18, 15, 12, 9, and 5 dozen, as well as for reusable plastic crates. A notable feature of the CSEG is it's VPN wifi module providing **FREE** level 1 phone tech support.

All BestPack units are available in our standard baked enamel finish and food-grade 304 stainless steel for 21 CFR 110 compliance.

RANDOM CARTONS



FULLY AUTOMATIC





TOP & BOTTOM SEAL

1,320 LBS


Shipping

Weight

110 VOLTS 60 HZ

Power Requirements

CARTON RANGE



Length (min. - max.) (6.0" - 25.5")

Width (min. - max.) (6.0" - 14.0")



Specifications based on CSEG11-2H

UP TO 27 CPM

Speed

85 PSI, 12+ SCFM Air Requirements

STANDARD FEATURES

- "Soft Touch" Pneumatic System designed to be Gentle on Cartons
- In-line Carton Closure
- Independent 3-stage Operation: Indexing, Flap Folding, & Sealing
- Allen-Bradley PLC w/ Ethernet Capabilities
- Indexer with Carton Centering Device
- Plastic Crate Pass-Through
- High Speed Motors for Belt Speed of 125 ft. per min.
- Tape Roll Lengths: 1,000 yd. & 1,500 yd.
- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs

OPTIONS

- Spare Parts Kit
- Allen Bradley PLC with Ethernet Capability
- Exit Conveyor
- Food Grade 304 Stainless Steel

- Carton Height Sensors
- UL Approved Electrical Parts
- Adjustable Bed Height from 25.5" to 30.0"
- Interlock Safety Gates
- Capable of Interchanging 2", 3", 4", & 6" Tape Heads
- Low Tape/No Tape on Carton/No Cut Sensors with Malfunction Alarm with Three-colored Light
- Heavy Duty Casters
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm
- VFD up to 25-30 cartons/min.
- VFD + Sidebelt Drive Upgrade up to 30+ cartons/min.

VFD - Variable Frequency Drive

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



SPARE TAPE HEAD Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SHORT OR LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT "Spare Parts Kits may vary based on machine" Minimize downtime with BestPack's Spare Parts Kit.



CARTON SEALING TAPE Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR CSEG MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
CSEG11-2H** 2" Tape Head	(99.2") x (38.2") x (75.9")	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(25.5" - 30.0")	Up to 27	1320
CSEG11-3H** 3" Tape Head	(99.2") x (38.2") x (75.9")	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(25.5" - 30.0")	Up to 27	1320

Information subject to change without notice.

*Outside Dimensions Only **High Speed



For more information please go to: WWW.BESTPACK.COM or call us at 1.888.588.2378

© 2024 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.