

AS-S Series Comparison Chart



Model	Machine Dimensions Length × Width × Height	Carton Range** Length (min max.) x Width (min max.) x Height (min max.)	Conveyor Height Adjustment Height (min max.)	Cartons per min.***	Shipping Weight (Ibs.)
AS 12-2 S 2" Tape Head	(70.2"*) x (26.5") x (68.0")	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	527
AS 12-3 S 3" Tape Head	(70.2"*) x (26.5") x (68.0"*)	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	527
AS 22-2 S 2" Tape Head	(77.7"*) x (33.8") x (69.0")	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	616
AS 22-3 S 3" Tape Head	(77.7"*) x (33.8") x (69.0"*)	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	616

Information subject to change without notice.

EXPERIENCE

U - Unlimited All Models available in High Speed * Safety Gates are an additional 20" Long ** Outside Dimensions Only *** Based on a 12" long carton

COMMU

WWW.BESTPACK.COM

VERSION 3.4_0622

E © 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

CO