


## **AS-S Series Comparison Chart**



Model	Machine Dimensions Length × Width × Height	Carton Range** Length (min max.) × Width (min max.) × Height (min max.)	Conveyor Height Adjustment Height (min max.)	Cartons per min.***	Shipping Weight (Ibs.)
AS 12-2 S <b>2" Tape Head</b>	(70.2"*) x (26.5") x (68.0")	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	527
AS 12-3 S 3" Tape Head	(70.2"*) x (26.5") x (68.0"*)	(6.0" - 25.5") x (6.0" - 14.0") x (6.5" - 20.0")	(22.5" - 30.0")	Up to 34	527
AS 22-2 S <b>2" Tape Head</b>	(77.7"*) x (33.8") x (69.0")	(6.0" - 27.5") x (6.0" - 20.0") x (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	616
AS 22-3 S <b>3" Tape Head</b>	(77.7"*) x (33.8") x (69.0"*)	(6.0" - 27.5") × (6.0" - 20.0") × (5.5" - 20.0")	(22.5" - 30.0")	Up to 34	616

Information subject to change without notice.

U - Unlimited All Models available in High Speed \* Safety Gates are an additional 20" Long \*\* Outside Dimensions Only \*\*\* Based on a 12" long carton