



AT4E S-FEED STAINLESS FULLY AUTOMATIC 4-EDGE CARTON SEALER WITH STRAIGHT FEED

The BestPack AT4E Stainless Steel Series is an operator free, four outer edge carton sealer with corner seals, using pressure sensitive tape. These carton sealers are designed to eliminate costly hand taping of the four outer edges where pilfer proofing and protection of your product from outside environment is necessary. The AT4E Stainless Steel model is designed for uniform edge sealing applications. This unit is designed with an automatic in-line 90 degree box turner.

All BestPack stainless steel sealers are made with food grade 304 stainless steel for 21 CFR 110 compliance and include 304 High Speed stainless steel tape heads. Units are available for either splash resistant or wash-down applications. This unit is also available in standard finish. Standard 3" Tape Head. stainless steel for 21 CFR 110 compliance and include 304 High Speed stainless steel tape heads. Units are available for either splash resistant or wash-down applications. This unit is also available for either splash resistant or wash-down applications. This unit is also available for either splash resistant or wash-down applications. This unit is also available for either splash resistant or wash-down applications. This unit is also available in standard finish. Standard 3" Tape Head.






UNIFORM CARTONS



110 V 60 HZ

Requirements

CARTON RANGE



Length (min. - max.) (10.3" - 23.5")

Width (min. - max.)



Height (min. - max.) (9.8" - 23.5")

Specifications based on AT4EL22-3S

EXPERIENC

WWW.BESTPACK.COM

UP TO 8 CPM

Speed

80 PSI, 10 SCFM Air Requirements

FULLY AUTOMATIC

1,550 - 1,970 LBS Shipping Weight

STANDARD FEATURES

- Heavy Duty 3mm Welded 304 Food Grade Stainless Steel Frame Including Upper Welded Legs
- Seals All Four Outside Carton Edges Including All Corners
- In-line 90 Degree Carton Turner
- Four Belt Drive System with 1-piece Molded Belts and V-belt Guide
- Top and Bottom Four 3" Pop-Out BestPack High Speed 304 Stainless Steel Tape Heads
- Low Tape/No Tape on Carton/No Cut Sensors with Malfunction Alarm and Three Color Light

- Motor Drive Uniform Height Adjustment
- Heavy Duty Upper Assembly Four Post System
- Heavy Duty Maintenance Free Oil-less Air Cylinder
- Aluminum Framed Interlock Safety Gates
 Where Needed
- Tape Roll Lengths: 1,000 yd.
- Quality UL Approved Electrical Parts

OPTIONS

Ε•

- Spare Parts Kit
- 304 Stainless MSD or 304 Stainless AS-S
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer

COMMI

VERSION 4.4_0822

COMMUNIT

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



304 STAINLESS STEEL SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SPARE PARTS KIT "Spare Parts Kits may vary based on machine" Minimize downtime with BestPack's Spare Parts Kit.



HIGH SPEED MOTOR High Speed Motor Upgrade (up to 125 ft.)



CARTON SEALING TAPE Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR AT4E S-FEED STAINLESS MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
AT4ES22-3S 3" Tape Head	(110.3") x (49.8") x (60.5")	(10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")	Determined at the time of order	Up to 8	1,970
		Also Available in L-Feed			
AT4EL22-3 3" Tape Head	(78.9") x (48.5") x (63.0")	(10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")	Determined at the time of order	Up to 8	1,550

Information subject to change without notice.



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.