



BESTPACK




BG16

**1.6 MIL (40 MICRON) TOTAL TAPE THICKNESS
22 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE**


BG16 is specially formulated for 100% recycled corrugated. By adding better quick tack properties to the benefits of acrylic, BG Tape is a perfect alternative to Hot Melt Tape.



EXTREME TEMPERATURES



GREAT INITIAL TACK



DOESN'T YELLOW TO UV

1.6 MIL (40 MICRON)*
Total Thickness

16 OZ/INCH WIDTH***
Peel Adhesion

0.7 MIL (18 MICRON)*
Adhesive Thickness


0.9 MIL (22 MICRON)*
Film Thickness

15 LBS/IN WIDTH**
Tensile Strength


110%**
Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- Good Initial Quick Tack
- Specially formulated ROHM & HAAS acrylic adhesive for use in hot & cold temperatures
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Specially formulated 110% elongation low stretch cast film increasing machine length roll performance
- Unlimited Shelf Life
- RoHS Compliant
- Available Hand & Machine Length Rolls
- Tape manufactured in ISO 9001 & 14001 Facilities

SERVICE TEMPERATURE

Minimum Temp.: **-30°F**
Maximum Temp.: **200°F**

USAGE & STORAGE TEMPERATURE

Minimum Temp.: **32°F**
Maximum Temp.: **150°F**

IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **77°F +/- 5°F**
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.