




BG16

1.6 MIL (40 MICRON) TOTAL TAPE THICKNESS
22 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE


BG16 is specially formulated for 100% recycled corrugated. By adding better quick tack properties to the benefits of acrylic, BG Tape is a perfect alternative to Hot Melt Tape.



EXTREME TEMPERATURES



GREAT INITIAL TACK




DOESN'T YELLOW TO UV


1.6 MIL (40 MICRON)* Total Thickness	16 OZ/INCH WIDTH*** Peel Adhesion	0.7 MIL (18 MICRON)* Adhesive Thickness
0.9 MIL (22 MICRON)* Film Thickness	15 LBS/IN WIDTH** Tensile Strength	110%** Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- Good Initial Quick Tack
- Specially formulated ROHM & HAAS acrylic adhesive for use in hot & cold temperatures
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Specially formulated 110% elongation low stretch cast film increasing machine length roll performance
- Unlimited Shelf Life
- RoHS Compliant
- Available Hand & Machine Length Rolls
- Tape manufactured in ISO 9001 & 14001 Facilities

SERVICE TEMPERATURE Minimum Temp.: -30°F Maximum Temp.: 200°F	USAGE & STORAGE TEMPERATURE Minimum Temp.: 32°F Maximum Temp.: 150°F	IDEAL STORAGE TEMPERATURE Ideal Storage Temp.: 77°F +/- 5°F Ideal Storage Humidity: 55% +/- 5%
--	---	---

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.