



# BP16

**1.6 MIL (40 MICRON) TOTAL TAPE THICKNESS**  
**25 MICRON CAST BOPP LOW ELONGATION FILM**  
**ROHM & HAAS ACRYLIC ADHESIVE**


BP16 is a premium box sealing tape used primarily for light carton sealing applications. This tape performs well in a broad temperature range.



**EXTREME TEMPERATURES**



**LONG SHELF LIFE**




**DOESN'T YELLOW TO UV**


|                                                |                                              |                                                   |
|------------------------------------------------|----------------------------------------------|---------------------------------------------------|
| <b>1.6 MIL (40 MICRON)*</b><br>Total Thickness | <b>16 OZ/INCH WIDTH***</b><br>Peel Adhesion  | <b>0.6 MIL (15 MICRON)*</b><br>Adhesive Thickness |
| <b>1.0 MIL (25 MICRON)*</b><br>Film Thickness  | <b>20 LBS/IN WIDTH**</b><br>Tensile Strength | <b>110%**</b><br>Elongation % At Break            |

Test Methods: \* ASTM D-3652; \*\* ASTM D-3759; \*\*\* ASTM D-3330


## AVAILABLE COLORS



## AVAILABLE LENGTHS



## AVAILABLE WIDTHS



## STANDARD FEATURES

- 25 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 15 micron water-based Rohm & Haas acrylic adhesive
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temperature.
- Unlimited Shelf Life
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Available Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.

|                                                                                          |                                                                                                     |                                                                                                                           |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>SERVICE TEMPERATURE</b><br>Minimum Temp.: <b>-30°F</b><br>Maximum Temp.: <b>200°F</b> | <b>USAGE &amp; STORAGE TEMPERATURE</b><br>Minimum Temp.: <b>32°F</b><br>Maximum Temp.: <b>150°F</b> | <b>IDEAL STORAGE TEMPERATURE</b><br>Ideal Storage Temp.: <b>77°F +/- 5°F</b><br>Ideal Storage Humidity: <b>55% +/- 5%</b> |
|------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.