




# BP20 ( Available in Printed Tape )

**2.0 MIL (50 MICRON) TOTAL TAPE THICKNESS**  
**28 MICRON CAST BOPP LOW ELONGATION FILM**  
**ROHM & HAAS ACRYLIC ADHESIVE**


BP20 is a premium box sealing tape used primarily for heavy duty carton sealing applications. This tape performs well in a broad temperature range.



**EXTREME TEMPERATURES**



**LONG SHELF LIFE**



**DOESN'T YELLOW TO UV**


<b>2.0 MIL (50 MICRON)*</b> Total Thickness	<b>20 OZ/INCH WIDTH***</b> Peel Adhesion	<b>0.9 MIL (22 MICRON)*</b> Adhesive Thickness
<b>1.1 MIL (28 MICRON)*</b> Film Thickness	<b>22 LBS/IN WIDTH**</b> Tensile Strength	<b>110%**</b> Elongation % At Break

Test Methods: \* ASTM D-3652; \*\* ASTM D-3759; \*\*\* ASTM D-3330


## AVAILABLE COLORS



## AVAILABLE LENGTHS



## AVAILABLE WIDTHS



## STANDARD FEATURES

- 28 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 22 micron water-based Rohm & Haas acrylic adhesive
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temperature.
- Unlimited Shelf Life
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Available Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets DFA food requirements for indirect food contact.

<b>SERVICE TEMPERATURE</b> Minimum Temp.: <b>-30°F</b> Maximum Temp.: <b>200°F</b>	<b>USAGE &amp; STORAGE TEMPERATURE</b> Minimum Temp.: <b>32°F</b> Maximum Temp.: <b>150°F</b>	<b>IDEAL STORAGE TEMPERATURE</b> Ideal Storage Temp.: <b>77°F +/- 5°F</b> Ideal Storage Humidity: <b>55% +/- 5%</b>
--	---	---

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.