




BP20 (Available in Printed Tape)

2.0 MIL (50 MICRON) TOTAL TAPE THICKNESS
28 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE


BP20 is a premium box sealing tape used primarily for heavy duty carton sealing applications. This tape performs well in a broad temperature range.



EXTREME TEMPERATURES



LONG SHELF LIFE



DOESN'T YELLOW TO UV


2.0 MIL (50 MICRON)* Total Thickness	20 OZ/INCH WIDTH*** Peel Adhesion	0.9 MIL (22 MICRON)* Adhesive Thickness
1.1 MIL (28 MICRON)* Film Thickness	22 LBS/IN WIDTH** Tensile Strength	110%** Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 28 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 22 micron water-based Rohm & Haas acrylic adhesive
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temperature.
- Unlimited Shelf Life
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Available Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.

SERVICE TEMPERATURE Minimum Temp.: -30°F Maximum Temp.: 200°F	USAGE & STORAGE TEMPERATURE Minimum Temp.: 32°F Maximum Temp.: 150°F	IDEAL STORAGE TEMPERATURE Ideal Storage Temp.: 77°F +/- 5°F Ideal Storage Humidity: 55% +/- 5%
--	---	---

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.