

BESTPACK'S FLAGSHIP PRESSURE SENSITIVE

ACRYLIC CARTON SEALING TAPE



TEMPERATURE-RESISTANT
WATER-BASED ACRYLIC

QUICK HIGHLIGHTS

- Unlimited Shelf Life
- UV Light Resistant
- Specially Formulated 140% Elongation Low Stretch Cast Film (Increasing Machine Length Roll Performance)
- Specially Formulated ROHM & HAAS (for use in Hot & Cold Temperature)
- RoHS Compliant
- Meets FDA Food Requirements for Indirect Food Contact

3.1 MIL (78 MICRON)* Total Thickness	27 oz/inch WIDTH*** Peel Adhesion	1.1 MIL (25 MICRON)* Adhesive Thickness
2.0 MIL (50 MICRON)* Film Thickness	31 LBS/IN WIDTH** Tensile Strength	140%** Elongation % At Break
Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330		

SERVICE TEMPERATURE
Minimum Temp.: -30°F Maximum Temp.: 200°F

USAGE & STORAGE TEMPERATURE
Minimum Temp.: 32°F Maximum Temp.: 150°F

IDEAL STORAGE TEMPERATURE
Ideal Storage Temp.: 77°F +/- 5°F Ideal Storage Humidity: 55% +/- 5%

AVAILABLE COLORS: CLEAR

AVAILABLE LENGTHS: 50m 100m 150m 914m

AVAILABLE WIDTHS: 48mm 72mm 96mm 144mm 288mm

BP31

**3.1 MIL (78 MICRON) TOTAL TAPE THICKNESS
50 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE**

BP31 is a premium box sealing tape used primarily for light carton sealing applications. This tape performs well in a broad temperature range.



LEARN MORE ABOUT OUR TAPE:
BROCHURES | MATERIAL SAFETY DATA SHEET | ROHS INFORMATION