




BESTPACK


HT16

1.6 MIL (40 MICRON) TOTAL TAPE THICKNESS
25 MICRON CAST BOPP LOW ELONGATION FILM
HOT MELT ADHESIVE

HT16 is an economy grade carton sealing tape, perfect for light-duty sealing.



HIGH SHEAR



GREAT INITIAL TACK



CONSISTENT & EASY RELEASE

1.6 MIL (40 MICRON)*
Total Thickness

30 OZ/INCH WIDTH***
Peel Adhesion

0.6 MIL (15 MICRON)*
Adhesive Thickness


1.0 MIL (25 MICRON)*
Film Thickness

19 LBS/IN WIDTH**
Tensile Strength


110%**
Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 25 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 15 micron Hot Melt Adhesive
- Available in Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.

SERVICE TEMPERATURE

Minimum Temp.: **30°F**
Maximum Temp.: **140°F**

USAGE & STORAGE TEMPERATURE

Minimum Temp.: **32°F**
Maximum Temp.: **104°F**

IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **77°F +/- 5°F**
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.