



# HT17

**1.61 MIL (41 MICRON) TOTAL TAPE THICKNESS**  
**24 MICRON CAST BOPP LOW ELONGATION FILM**  
**HOT MELT ADHESIVE**

HT17 is an economy grade carton sealing tape, perfect for light-duty sealing.



HIGH SHEAR



GREAT INITIAL TACK



CONSISTENT & EASY RELEASE

**1.61 MIL (41 MICRON)\***  
Total Thickness

**46 OZ/INCH WIDTH\*\*\***  
Peel Adhesion

**0.65 MIL (17 MICRON)\***  
Adhesive Thickness


**0.96 MIL (24 MICRON)\***  
Film Thickness

**8.6 LBS/IN WIDTH\*\***  
Tensile Strength

**165%\*\***  
Elongation % At Break

Test Methods: \* ASTM D-3652; \*\* ASTM D-3759; \*\*\* ASTM D-3330

## AVAILABLE COLORS



## AVAILABLE LENGTHS




914m & 1371m



1500m & 1828m

## AVAILABLE WIDTHS



## STANDARD FEATURES

- 24 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 17 micron hot melt adhesive
- Specially formulated 165% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufacture in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.
- Available in Hand & Machine Length Rolls

### SERVICE TEMPERATURE

Minimum Temp.: **30°F**  
Maximum Temp.: **140°F**

### USAGE & STORAGE TEMPERATURE

Minimum Temp.: **50°F**  
Maximum Temp.: **110°F**

### IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **40°F +/- 5°F**  
Ideal Storage Humidity: **40% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.