



HT30

3.0 MIL (76 MICRON) TOTAL TAPE THICKNESS
50 MICRON CAST BOPP LOW ELONGATION FILM
HOT MELT ADHESIVE

HT30 is a heavy duty grade carton sealing tape for those applications needing a strong and sturdy seal.



HIGH SHEAR



GREAT INITIAL TACK




CONSISTENT & EASY RELEASE


3.0 MIL (76 MICRON)* Total Thickness	60 OZ/INCH WIDTH*** Peel Adhesion	1.0 MIL (26 MICRON)* Adhesive Thickness
2.0 MIL (50 MICRON)* Film Thickness	33 LBS/IN WIDTH** Tensile Strength	140%** Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 50 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 26 micron hot melt adhesive
- Specially formulated 140% elongation low stretch cast film increasing Machine Length Roll performance.
- Length Roll performance.
- RoHS Compliant
- Tape manufacture in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.
- Available in Hand & Machine Length Rolls

SERVICE TEMPERATURE Minimum Temp.: 30°F Maximum Temp.: 140°F	USAGE & STORAGE TEMPERATURE Minimum Temp.: 32°F Maximum Temp.: 104°F	IDEAL STORAGE TEMPERATURE Ideal Storage Temp.: 77°F +/- 5°F Ideal Storage Humidity: 55% +/- 5%
---	---	---

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.