



MS1E

MANUAL SIDEDRIVE 1 EDGE CARTON SEALER

The BestPack[™] MS1E Series is a 1-edge high-speed semi-automatic uniform carton sealer using pressure sensitive tape. The MS1E is available in either 1-edge top left or 1-edge top right. This 1-edge sealer is an operator fed adjustable sealer that can also be converted to an operator free adjustable 1-edge sealer with the addition of a matching adjustable indexer. Depending on the motor drive speed used the MS1E can reach cartons speeds of over 45 cartons per minute. This sealer excels at one edge sealing clamshell, flap tuck and flap edge lock type cartons both in corrugated and chipboard.







OPERATOR REQUIRED UNIFORM CARTONS

50 PSI

5 SCFM

Air Requirements


1-EDGE SEAL

350 LBS Shipping Weight

110 VOLTS 60 HZ

1.9 A, 122 watts/motor Power Requirements

CARTON RANGE



Length (min. - max.)

(7.0" - U)

Width (min. - max.)

(1.72" - 5.5")

Height (min. - max.)

(4.0" - 21.75")

Specifications based on MS1ETL22-2

EXPERIENC

WWW.BESTPACK.COM

STANDARD FEATURES

UP TO 45 CPM

Speed

- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Side Belt Drive
- Top 1 Edge Seal
- Adjustable Bed Height from 22.5" to 30.0"
- Exclusive 2" Pneumatic Pop-out Pressure Sensitive "High Speed" BestPack Tape Head
- Tape Roll Lengths: 1,000 yd. and 1,500 yd.
- Front Interlock Safety Gates
- UL Approved Electrical Parts
- Maintenance Free, Oil-less Cylinders

OPTIONS

- Second Timer for Multi-able Tabs on the Single Carton Edge
- Spare Parts Kit

Ε

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters

CU

- High Speed Motor Upgrade (Up to 125 ft./mm.)
- Indexer (for fully automatic function)
- Food grade 304 Stainless Steel
- Low or No Tape Sensor and Alarms

COMMUNIT

VERSION 4.3_0622

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape

in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



FOOD GRADE 304 STAINLESS STEEL This machine is available in 304 stainless steel which is food grade safe for food applications.



SPARE PARTS KIT "Spare Parts Kits may vary based on machine" Minimize downtime with BestPack's Spare Parts Kit.



CARTON SEALING TAPE Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR High Speed Motor Upgrade (up to 125 ft.)

POPULAR MS1E MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH X WIDTH X HEIGHT	CARTON RANGE LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
MS1ETL22-2 2" Tape Head Top Left Edge	(41.5") x (26.0") x (62.25" - 68.75")	(7.0" - U) x (1.72" - 5.5") x (4.0" - 21.75")	(23.5" - 30.0")	Up to 45	350
MS1ETR22-2 2" Tape Head	(41.5") × (26.0") × (62.25" - 68.75")	(7.0" - U) x (1.72" - 5.5") x (4.0" - 21.75")	(23.5" - 30.0")	Up to 45	350

Information subject to change without notice.

All Models Available in High Speed & Food Grade 304 Stainless Steel



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.