




MS2B2T

MANUAL SIDEDRIVE 2 BOTTOM & 2 TOP CARTON SEALER

The BestPack™ MS2B2T Series carton sealer is operator-fed and adjustable. It is designed to lay two strips of tape on the bottom and two strips of tape top of the carton. This becomes necessary where the major flaps do not meet in the middle of the carton, and the cost of staples is not acceptable. This series sealer eliminates all together the need for staples or glue on the bottom and the top of the carton. The sealer has four tape heads, with two side belts driven by two electric 110V UL approved motors.



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 40 CPM

Speed


N/A

Air Requirements

435 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(10.0" - 21.5")

Height (min. - max.)
(5.5" - 30.0")

Specifications based on MS2B2T23-2

STANDARD FEATURES

- Heavy duty 2mm welded frame including upper welded legs
- Side belt drive system with idler rollers behind the 1-piece die molded belts that also includes V-belt guide
- Lays two strips of tape on the bottom and two strips of tape on the top of the carton
- Accepts 2" and 3" Pop-out BestPack High Speed Tape Heads
- Upper Side Compression Unit
- Width and Height Adjustment Crank Handles can be Mounted on Either Side of the Sealer
- Electrical On/Off Box can also be Easily Mounted on Either Side of the Sealer (Left Side is Standard)
- Adjustable Bed Height for MS2B2T23: 20.5" to 30.0"
- Tape Roll Lengths: 1,000 yd., 1,500 yd., and 2,000 yd.
- Upper Mast is Tapped and Drilled that can be Raised (Un-bolted, Raised and Re-bolted) for an Extra 4" Carton Height if Needed
- Quality UL Approved Electrical Parts

OPTIONS

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters
- 3-Flap Folder
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SHORT OR LONG INFEEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



3 FLAP FOLDER

This accessory adds automation to your adjustable manual carton sealer. The operator only need to close the rear minor flap and push the carton into the unit, the carton sealer does the rest.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR MS2B2T MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.**	SHIPPING WEIGHT (LBS)
MS2B2T23-2 2" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (10.0" - 21.5") x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435
MS2B2T23-3 3" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (10.0" - 21.5") x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435

Information subject to change without notice.
Top Gap Width Range (3.22" - 6.5")
Bottom Gap Width Range (4.0" - 6.0")

* Outside Dimensions Only
** Based on Customer Application
All Models Available in High Speed & Food Grade 304 Stainless Steel



For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**