



# **MSAG Series**

### MANUAL SIDEDRIVE FOR AGRICULTURE PRODUCTS

The BestPack™ MSAG is a Semi-Automatic Uniform Tape Carton Sealer. The MSAG is designed for unique applications where the sealer needs to place two strips of tape on the top of the carton, even out to the top edges of the carton. Yet still seal in the center of the carton on the bottom. The upper assembly and bottom assembly can accept center seal with 2", 3" and 6" tape heads, or double sealing the top of the carton that can be accomplished with either 2" tape heads or 3" tape heads. A top 3-flap folder and front extended side belts are included.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



**OPERATOR REQUIRED** 



**UNIFORM CARTONS** 



2 TOP & 1 BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements **UP TO 35 CPM** 


Speed

N/A

Air Requirements 575 LBS

Shipping Weight

# **CARTON RANGE**



Length (min. - max.)
(6.0" - U)

Width (min. - max.) **(8.5" - 31.0")** 

Height (min. - max.)

(6.25" - 20.25")

Specifications based on MSAG-3HEB

## STANDARD FEATURES

- Semi-Automatic Uniform Carton Sealer
- Extended Side Belt Drives
- Top 3-Flap Folder
- Adjustable Acme Screw Drive Upper Assembly that Allows for Top Center Seal, or Splits Apart for Double Taping on Top Even Out to the Outside Edges of the Carton
- Upper Assembly Accepts 2", 3", and 6" High Speed Tape Heads for Top Center Seal. It Also Accepts 2" and 3" Tape Heads for Double Top Seal
- Bottom Center Seals with either 2", 3" or 6" High Speed Tape Heads
- Tape Roll Lengths: 1,000 yd. and 1,500 yd. (1,000 yd. only for 6")

- Upper Side Compression Unit
- Width/Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- High Speed Motors
- Adjustable Bed Height from 20.5" to 30.0"
- Electrical On/Off Box can be Mounted on Either Side of the Sealer
- Heavy Duty Frame
- UL Approved Electrical Parts

### **OPTIONS**

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Locking Casters

Right Justified

WWW.BESTPACK.COM VERSION 4.3\_0622

# **EXTRA ACCESSORIES TO IMPROVE EFFICIENCY**



#### **LOCKING CASTERS**

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



#### **SPARE TAPE HEAD**

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



#### SHORT OR LONG INFEED/EXIT **CONVEYOR W/L-BRACKET STABILIZER**

This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



#### SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



(its may vary based on machine) Minimize downtime with BestPack's Spare Parts Kit.



#### **FOOD GRADE 304 STAINLESS STEEL**

This machine is available in 304 stainless steel which is food grade safe for food applications.



#### **CARTON SEALING TAPE**

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

# **POPULAR MSAG MODELS**

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x width (min max.) x height (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.***	SHIPPING WEIGHT (LBS)
MSAG-3HEB**	(58 5") x (43 3") x (65 0")	(6 0" - U) x (8 5" - 31 0") x (6 25" - 20 25")	(20.5" - 30.0")	Up to 35	575

3" Tape Head

Information subject to change without notice.

**U** - Unlimited \* Outside Dimensions Only \*\* High Speed \*\*\* Based on Customer Application

