



MSD-6

MANUAL SIDEDRIVE DUAL MAST CARTON SEALER

The BestPack™ 6" Series Semi-Automatic Uniform Tape Carton Sealer is an operator fed adjustable carton sealer using 6" wide tape to seal the top and bottom of a carton. 6" wide tape helps with security, tamper protection, and pilferage prevention, and also effectively seals cartons that are overly heavy, over-filled, or otherwise difficult to keep sealed.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance. The MSD 6" series sealer also accepts 4", 3" and 2" tape heads with optional skid plate adapters.



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

UP TO 40 CPM

Speed


N/A

Air Requirements

425 LBS

Shipping Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.) (8.25" - 20.0")

Height (min. - max.) (3.5" - 20.5")

Specifications based on MSD22-6

STANDARD FEATURES

- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Side Belt Drive System with Idler Rollers Behind the 1-piece Die Molded Belts that also Includes V-belt Guide
- Accepts 6", 4", 3", and 2" Pop-out BestPack High Speed Tape Heads
- Telescopic Mast Design with Screw Drive Shafts and a Unique 4 Roller Upper Side Compression Unit
- Width/Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Adjustable Bed Height from 23.5" to 30.0"

- Electrical On/Off Box can also be Easily Mounted on Either Side of the Sealer (Left Side is Standard)
- Tape Roll Lengths: 1,000 yd. and 1,500 yd.
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Exclusive Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise
- Reduction Arm
- Quality UL Approved Electrical Parts

OPTIONS

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- 3 Flap Folder
- Interlock Safety Gates
- Motorized Height and/or Width Adjustment
- Food Grade 304 Stainless Steel

WWW.BESTPACK.COM VERSION 4.2_0921

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SHORT OR LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARF PARTS KIT

Spare Parts Kits may vary based on machine Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



3 FLAP FOLDER

This accessory adds automation to your adjustable manual carton sealer. The operator only need to close the rear minor flap and push the carton into the unit, the carton sealer does the rest.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR MSD-6 MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
MSD22-6 6" Tape Head	(39.5") x (32.8") x (70.3")	(6.0" - U) × (8.25" - 20.0") × (3.5" - 20.5")	(23.5" - 30.0")	Up to 40	425
MSD22-6M** 6" Tape Head	(39.5") × (32.8") × (70.3")	(6.0" - U) × (8.25" - 20.0") × (3.5" - 20.5")	(23.5" - 30.0")	Up to 40	425

Information subject to change without notice.

* Outside Dimensions Only U - Unlimited

 ** Motorized assist tape heads when high speed motors and/or acrylic tapes are used

