

# MSD-6 MANUAL SIDEDRIVE DUAL MAST CARTON SEALER

The BestPack<sup>™</sup> 6" Series Semi-Automatic Uniform Tape Carton Sealer is an operator fed adjustable carton sealer using 6" wide tape to seal the top and bottom of a carton. 6" wide tape helps with security, tamper protection, and pilferage prevention, and also effectively seals cartons that are overly heavy, over-filled, or otherwise difficult to keep sealed.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance. The MSD 6" series sealer also accepts 4", 3" and 2" tape heads with optional skid plate adapters.



**OPERATOR REQUIRED** 



**UNIFORM CARTONS** 



**TOP & BOTTOM SEAL** 

425 LBS


Shipping

Weight

### 110 VOLTS 60 HZ

Power Requirements

## CARTON RANGE



Length (min. - max.)

(6.0" - U)

Width (min. - max.)

(8.25" - 20.0")

Height (min. - max.)

(3.5" - 20.5")

Specifications based on MSD22-6

EXPERIENCE

### WWW.BESTPACK.COM

### UP TO 40 CPM

Speed

STANDARD FEATURES

Including Upper Welded Legs

High Speed Tape Heads

**Compression Unit** 

Heavy Duty 2mm CNC Cut and Welded Frame

 Side Belt Drive System with Idler Rollers Behind the 1-piece Die Molded Belts that also Includes

• Accepts 6", 4", 3", and 2" Pop-out BestPack

• Width/Height Adjustment Handle can be Mounted

Telescopic Mast Design with Screw Drive

on Either Side of the Carton Sealer

Shafts and a Unique 4 Roller Upper Side

Adjustable Bed Height from 23.5" to 30.0"

**N/A** Air Requirements

> • Electrical On/Off Box can also be Easily Mounted on Either Side of the Sealer (Left Side is Standard)

- Tape Roll Lengths: 1,000 yd. and 1,500 yd.
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Exclusive Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise
- Reduction Arm
- Quality UL Approved Electrical Parts

**OPTIONS** 

V-belt Guide

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters

 $\left( \right)$ 

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- 3 Flap Folder
- Interlock Safety Gates
- Motorized Height and/or Width Adjustment

COMMUNIT

• Food Grade 304 Stainless Steel

VERSION 4.3\_0622

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

## **EXTRA ACCESSORIES TO IMPROVE EFFICIENCY**



LOCKING CASTERS The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



#### SHORT OR LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



**SPARE PARTS KIT** "Spare Parts Kits may vary based on machine" Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL This machine is available in 304 stainless steel which is food grade safe for food applications.



#### 3 FLAP FOLDER

This accessory adds automation to your adjustable manual carton sealer. The operator only need to close the rear minor flap and push the carton into the unit, the carton sealer does the rest.



**CARTON SEALING TAPE** Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR High Speed Motor Upgrade (up to 125 ft.)

## **POPULAR MSD-6 MODELS**

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
MSD22-6 6" Tape Head	(39.5") x (32.8") x (70.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30.0")	Up to 40	425
MSD22-6M** 6" Tape Head	(39.5") x (32.8") x (70.3")	(6.0" - U) x (8.25" - 20.0") x (3.5" - 20.5")	(23.5" - 30.0")	Up to 40	425

Information subject to change without notice.

\* Outside Dimensions Only U - Unlimited

\*\* Motorized assist tape heads when high speed motors and/or acrylic tapes are used



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378** 

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.