



MTLW


MANUAL TOP DRIVE LOW PROFILE CARTON SEALER

The BestPack™ MTLW Series are Semi-Automatic Adjustable Tape Carton Sealers engineered for economical, effective operator-fed closure applications. The MTLW's air-driven brush tucks the leading and trailing tabs that hang over the bottom of the carton. This brush facilitates top sealing of cartons from a min. height of 1/2" high, three inches lower than the MTD's min. height of 3.5".

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power
Requirements

UP TO 40 CPM

Speed


60-75 PSI, 2-3 SCFM

Air
Requirements

388-416 LBS

Shipping
Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(8.2" - 19.7")

Height (min. - max.)
(0.5" - 20.3")

Specifications based on MTLW22-2

STANDARD FEATURES

- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Four Belt Drive System (2 Top and 2 Bottom) with Idler Rollers Behind the 1-piece Die Molded Belts that also Includes V-belt Guide
- Air-Driven Bottom Brush that Allows for Low Top Seal Down to 0.5" in Height
- Top and Bottom Tape Head Included for Top and Bottom Seal Down to 3.5" in Height
- Accepts 2" or 3" Pop-out BestPack High Speed Tape Heads
- Upper Side Compression Unit
- Individually Adjustable Side Width Guide Rails
- Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Electrical On/Off Box can be Mounted on Either Side of the Sealer (Left Side is Standard)
- Adjustable Bed Height from 20.5" to 30.0"
- Tape Roll Lengths: 1,000 yd. and 1,500 yd.
- UL Approved Electrical Parts

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



SAFETY GATES

Aluminum frame interlock safety gates can be added to the carton sealer for an extra layer of protection. These interlock safety gates protect the operator from all of the moving parts of the carton sealer.



LOW OR NO TAPE SENSOR

The low tape light allows the operator to prepare a new roll of tape. The no tape alarm will inform the operator of the error so that the carton may be resealed.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR MTLW MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.**	SHIPPING WEIGHT (LBS)
MTLW22-2 2" Tape Head	(46.1") x (33.5") x (55.5")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	388
MTLW22-3 3" Tape Head	(46.1") x (33.5") x (55.5")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	388
MTLW32-2 2" Tape Head	(46.1") x (43.0") x (55.5")	(6.0" - U) x (8.2*** - 30.0") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	416
MTLW32-3 3" Tape Head	(46.1") x (43.0") x (55.5")	(6.0" - U) x (8.2*** - 30.0") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	416

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
*** Based on Customer Application



BESTPACK

For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.