



MTSS


MANUAL SIDE SEALING CARTON SEALER

The BestPack™ MTSS Series is an operator-fed, adjustable carton sealer designed to effectively seal cartons that need to be filled from the side as a result of the product's weight, shape, and size.


All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



UNIFORM CARTONS



SIDE SEAL

110 VOLTS 60 HZ

Power
Requirements

UP TO 40 CPM

Speed


N/A

Air
Requirements

548-688 LBS

Shipping
Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(7.5" - 21.0")

Height (min. - max.)
(4.5" - 19.5")

Specifications based on MTSS22-2

STANDARD FEATURES

- Each Side Tape Head is Individually Adjustable.
- The Individual Adjustability Allows Complete Control Over the Location Where the Tape can be Applied on the Side of the Carton. This Allows for the Taping of Side RSC and FOL Cartons.
- 4 Belt Drive - 2 Top and 2 Bottom Belts
- Adjustable Bed Height from 20.5" - 30.0"
- The MTSS Series are Designed with Four Adjustable Legs for Quick, Easy Height Adjustment to Production Lines.
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical On/Off Box can be Mounted on Either Side of the Sealer

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Heavy Duty Dual Locking Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Low or No Tape Sensor
- Stainless Steel

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine

Minimize downtime with BestPack's Spare Parts Kit.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR MTSS MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
MTSS22-2/3 2" or 3" Tape Head	(45.5") x (33.6") x (53.0")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 19.5")	(20.5" - 30")	Up to 40	548
MTSS33-2/3 2" or 3" Tape Head	(45.5") x (52.0") x (71.0")	(6.0" - U) x (14.3" - 31.0") x (8.5" - 30.0")	(20.5" - 30")	Up to 40	688

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only



BESTPACK

For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.