




RS-6 COMPARISON CHART

RANDOM SIDEDRIVE CARTON SEALER



OPERATOR REQUIRED



RANDOM CARTONS



TOP & BOTTOM SEAL

Can't find what your looking for? Customize this model specific to your application. Contact your local BestPack sales representative for more information or inquire at:
sales@bestpack.com

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
RS22-6 2" Tape Head	(42.9") x (34.8") x (71.8")	(6.0" - U) x (8.5" - 21.0") x (4.0" x 20.5")	(20.5" - 30.0")	Up to 15	475
RS22-6M** 6" Motor Assist Tape Head	(42.9") x (34.8") x (71.8")	(6.0" - U) x (8.5" - 21.0") x (4.0" x 20.5")	(20.5" - 30.0")	Up to 15	475

Information subject to change without notice.

U - Unlimited

* Outside Dimensions Only

** Motorized Assist Tape Heads When High Speed Motors and/or Acrylic Tapes are Used
 All Models Available in High Speed & Food Grade 304 Stainless Steel