

RSL RANDOM SIDEDRIVE LOW PROFILE CARTON SEALER

The BestPack[™] RSL Series is a Semi-Automatic Random Tape Carton Sealers designed to seal very low profile cartons in addition to the wide range expected of a random carton sealer. Build for speed and durability, the RSL's low profile feature allows for the effective sealing of cartons at a minimum height of 2.5". The RSL is capable of sealing cartons up to 20.5" tall as well.



OPERATOR REQUIRED



RANDOM CARTONS



TOP & BOTTOM SEAL

450 LBS


Shipping

Weight

110 VOLTS 60 HZ

Power Requirements

CARTON RANGE



Length (min. - max.) (6.0" - U)

Width (min. - max.) (5.7" - 21.0")

Height (min. - max.)

(2.5" - 20.5")

Specifications based on RSL22-2

EXPERIENCE

WWW.BESTPACK.COM

UP TO 12 CPM

55-60 PSI, 5 SCFM Air Requirements

• Adjustable Bed Height from 20.5" to 30.0"

- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Quality UL Approved Electrical Parts
- Exclusive 2" and 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise **Reduction Arm**

OPTIONS

Air-cylinders

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters

()

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

COMMUNIT

VERSION 4.3_0622

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

Speed

• Heavy Duty 2mm CNC Cut and Welded Frame

• Random Side Belt Drive System with 1-piece

• Electrical On/Off Box can also be Easily Mounted

Upper Random Mast is Tapped and Drilled that

can be Raised (Un-bolted, Raised and Re-bolted)

on Either Side of the Sealer (Left Side is Standard)

STANDARD FEATURES

Including Upper Welded Legs

Molded Belts and V-belt Guide

Seals Cartons as Low as 2.5" in Height

Uses Heavy Duty SMC Oil-less Cushioned

for an Extra 4" Carton Height if Needed

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SHORT INFEED/EXIT CONVEYOR WITH L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT *Spare Parts Kits may vary based on machine* Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL This machine is available in 304 stainless steel which is food grade safe for food applications.



HIGH SPEED MOTOR High Speed Motor Upgrade (up to 125 ft.)



LONG INFEED/EXIT CONVEYOR WITH L-BRACKET STABILIZER This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



CARTON SEALING TAPE Put high quality tape on your

BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

POPULAR RSL MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
RSL22-2 2" Tape Head	(60.4") x (34.8") x (71.8")	(6.0" - U) x (5.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30.0")	Up to 12	450
RSL22-3 3" Tape Head	(60.4") × (34.8") × (71.8")	(6.0" - U) x (6.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30.0")	Up to 12	450

Information subject to change without notice.

U - Unlimited * Outside Dimensions Only

All Models Available in High Speed & Food Grade 304 Stainless Steel



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**

© 2022 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.