



RS Bottom Only


BOTTOM ONLY CARTON SEALER

The BestPack™ RS20 Series is a Semi-Automatic Random Bottom Carton Sealer designed to fulfill light to heavy duty random bottom sealing needs. This unit is incredibly effective when random bottom carton sealing volume has become too large for hand sealing.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



RANDOM CARTONS



BOTTOM SEAL

110 VOLTS 60 HZ

Power
Requirements

UP TO 15 CPM

Speed


80 PSI, 5SCFM

Air
Requirements

330-380 LBS

Shipping
Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(4.25" - 20.0")

Height (min. - max.)
(4.0+)"

Specifications based on RS20-2

STANDARD FEATURES

- Side Belt Drive
- Adjustable Bed Height from 20.5" - 30"
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Maintenance Free Oil-less Air Cylinder
- Heavy Duty Frame
- UL Approved Electrical Parts
- Electrical On/Off Box can be Mounted on Either
- Side of the Carton Sealer
- Tool Kit & Operation Manual
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Interlock Safety Gates
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel
- Heavy-Duty Locking Casters
- Low Tape or No Tape Sensor

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



SHORT OR LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short or 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR RS BOTTOM ONLY MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
RS20-2 2" Tape Head	(42.9") x (30.0") x (28.8")	(6.0" - U) x (4.25" - 20.0") x (4.0+)"	(20.5" - 30.0")	Up to 15	318
RS20-3 3" Tape Head	(42.9") x (30.0") x (28.8")	(6.0" - U) x (5.25" - 21.0") x (4.0+)"	(20.5" - 30.0")	Up to 15	318
RS30-2 2" Tape Head	(42.9") x (39.4") x (28.8")	(6.0" - U) x (4.5" - 30.0") x (4.0+)"	(20.5" - 30.0")	Up to 15	380
RS30-3 3" Tape Head	(42.9") x (39.4") x (28.8")	(6.0" - U) x (5.5" - 30.0") x (4.0+)"	(20.5" - 30.0")	Up to 15	380

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only



BESTPACK

For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**

© 2024 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.