

MSDBF

Manual Sidedrive Dual Mast Flap Folder

The BestPack™ MSDBF sealer is a unique multi-purpose machine. Featuring a convenient top 3-flap folder and bottom T-rail leading to an extended side-drive system, the MSDBF enables a person to efficiently erect, pack, flap fold, and seal a carton in one station. Dual telescopic masts allow for an extra 4" carton height extension on the upper assembly and two 110V UL-approved electric motors power the extended side belt drive.

Our MSDBF line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

Features

- Designed for Uniform Applications Capable of Interchanging: 2" or 3" Tape Heads
- Extended Two Side Belts
- Uniform Top & Bottom Flap Folder
- Telescopic Mast Design
- Attached T-Rail Packing Station (Additional T-Rail Adaptors may be Needed Depending on Box Sizes)
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- Adjustable Bed Height 23.5" to 30.0"
- Width/Height Adjustment Either Side of Carton Sealer
- Exclusive 4 Roller Upper Side Compression Unit
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame

- UL Approved Electrical Parts
- Electrical On/Off Box can be Mounted on Either Side of Machine

Options

- Spare Parts Kit
- T-Rail Adaptors (Needed Depending on Carton Sizes)
- Motorized Height and/or Width Adjustment
- Exit Conveyor
- Locking Casters w/ Support Brackets
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters
w/ Support Brackets



Exit Conveyor



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Food Grade 304 Stainless Steel
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz

Power Requirements

Up to 15 Cartons/min.

Speed

N/A

Air Requirements

420-648 lbs

Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
MSDBF22-2 2" Tape Head	(99.6") x (32.8") x (70.3")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0" - 19.6")	(23.5" - 30.0")	Up to 15	420
MSDBF22-3 3" Tape Head	(99.6") x (32.8") x (70.3")	(7.8" - 23.6") x (7.8" - 19.6") x (4.0" - 19.6")	(23.5" - 30.0")	Up to 15	420
MSDBF32-2 2" Tape Head	(125.0") x (43.8") x (70.3")	(14.0" - 48.0") x (12.0" - 30.0") x (6.0" - 19.6")	(23.5" - 30.0")	Up to 15	648
MSDBF32-3 3" Tape Head	(125.0") x (43.8") x (70.3")	(14.0" - 48.0") x (12.0" - 30.0") x (6.0" - 19.6")	(25.8" - 30.0")	Up to 15	648

Information subject to change without notice.

*Outside Dimensions Only
All specifications capable of customization.