

C-SERIES CARTON SEALER APPLICATION FORM

END USER INFORMATION

Company Name

Address

City State Zip Code

Contact Name & Title

Telephone No.

E-Mail

DISTRIBUTOR INFORMATION

Company Name


Address

City State Zip Code

Contact Name & Title

Telephone No.

E-Mail



LENGTH	WIDTH	HEIGHT	WEIGHT	% OF PRODUCTION
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>

CARTON STATUS

Filled

Underfilled

Overfilled

Re-Used

SAMPLE CARTONS SENT

Yes No

CARTON INFORMATION

CARTONS

RSC

HSC

Other

CARTON TO BE TAPED:

Top & Bottom Bypass Needed

Top Only

Bottom Only

4-Edge Seal

TAPE:

2" (48mm)

3" (72mm)

4" (96mm)

6" (144mm)

Packing Room Temperature:

PACKING ROOM CONDITIONS:

Normal Wet Dusty Corrosive

POWER REQUIREMENTS

FLOW DIRECTION STANDING IN FRONT OF ELECTRICAL BOX:

Right to Left (Standard)

Left to Right

ELECTRICAL REQUIREMENTS

Volts

Phase

AIR REQUIREMENTS

IS THERE AN AIR DRYER?

Yes

No

PSI:

SCFM:

CARTONS PER

Minute: Shift:

Hour: Day:

RECOMMENDED MODEL:

CONVEYOR HEIGHT

Conveyor Height:

Infeed Conveyor Powered

Exit Conveyor Powered

FACILITY INFORMATION

ARE THESE MACHINES GOING INTO A NEW OR EXISTING FACILITY?

FACILITY TECHNICAL SUPPORT:

<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
Number of Techs with Mechanical Knowledge	Number of Techs with Electrical Knowledge	Number of Techs with PLC Knowledge	Number of Engineers

CAN PRODUCTION ACCOMMODATE DOWN TIME FOR TAPE ROLL CHANGES?

Yes No

CAN PRODUCTION ACCOMMODATE DOWN TIME FOR MAINTENANCE?

Yes No

For fully automatic applications it is the responsibility of the end user to inform their corrugator that the cartons need to be well scored, with proper glue joints, and 3/8" or larger slots. Applications for CSX type fully automatic random sealers require minor flaps to be slightly tucked inside major flaps before closing.

Comments

Completed By

Date

PLEASE EMAIL COMPLETED FORM TO SALES@BESTPACK.COM

BestPackTM
the total tape sealing solution

For more information please go to:
WWW.BESTPACK.COM or call us at **1.888.588.2378**

© 2019 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.