

## MTLW

### Manual Top Drive Low Profile Carton Sealer

The BestPack™ MTLW Series are Semi-Automatic Adjustable Tape Carton Sealers engineered for economical, effective operator-fed closure applications. The MTLW's air-driven brush tucks the leading and trailing tabs that hang over the bottom of the carton. This brush facilitates top sealing of cartons from a min. height of 1/2" high, three inches lower than the MTD's min. height of 3.5".

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance and come with high speed tape heads with tab adjustment. Available with 2" or 3" tape heads.



## Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Top & Bottom Seal

## Features

- Heavy Duty 2mm CNC Cut and Welded Frame Including Upper Welded Legs
- Four Belt Drive System (2 Top and 2 Bottom) with Idler Rollers Behind the 1-piece Die Molded Belts that also Includes V-belt Guide
- Air-Driven Bottom Brush that Allows for Low Top Seal Down to 0.5" in Height
- Top and Bottom Tape Head Included for Top and Bottom Seal Down to 3.5" in Height
- Accepts 2" or 3" Pop-out BestPack High Speed Tape Heads
- Upper Side Compression Unit
- Individually Adjustable Side Width Guide Rails
- Height Adjustment Crank Handles can be Mounted on Either Side of the Sealer

- Electrical On/Off Box can also be Easily Mounted on Either Side of the Sealer (Left Side is Standard)
- Adjustable Bed Height for the MTLW is 20.5" to 30.0"
- Tape Roll Lengths: 1,000 yd. and 1,500 yd.
- Quality UL Approved Electrical Parts

## Options

- Infeed/Exit Conveyor w/L-Bracket Stabilizer
- Heavy Duty Dual Locking Casters
- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

# Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Infeed/Exit Conveyor  
w/Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft.)
- Stainless Steel
- Low Tape/No Tape Sensors
- Interlock Safety Gates
- Carton Sealing Tape

## Machine & Carton Specifications

**110 Volts 60 Hz**  
Power Requirements

**Up to 40 Cartons/min.**  
Speed

**60-75 PSI**  
2-3 SCFM  
Air Requirements

**388-450 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
MTLW22-2 <b>2" Tape Head</b>	(46.1") x (33.5") x (55.5")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	388
MTLW22-3 <b>3" Tape Head</b>	(46.1") x (33.5") x (55.5")	(6.0" - U) x (8.2*** - 19.7") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	388
MTLW32-2 <b>2" Tape Head</b>	(46.1") x (43.0") x (55.5")	(6.0" - U) x (8.2*** - 30.0") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	450
MTLW32-3 <b>3" Tape Head</b>	(46.1") x (43.0") x (55.5")	(6.0" - U) x (8.2*** - 30.0") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	450

All specifications capable of customization or subject to change without notice.

U - Unlimited  
All Models available in High Speed & Food Grade 304 Stainless Steel  
\* Outside Dimensions Only  
\*\* With Narrow Side Rail Adapter