



## BP20 ( Available in Printed Tape )

**2.0 MIL (50 MICRON) TOTAL TAPE THICKNESS**  
**28 MICRON CAST BOPP LOW ELONGATION FILM**  
**ROHM & HAAS ACRYLIC ADHESIVE**

BP20 is a premium box sealing tape used primarily for heavy duty carton sealing applications. This tape performs well in a broad temperature range.



EXTREME TEMPERATURES



LONG SHELF LIFE



DOESN'T YELLOW TO UV

**2.0 MIL (50 MICRON)\***  
Total Thickness

**20 OZ/INCH WIDTH\*\*\***  
Peel Adhesion

**0.9 MIL (22 MICRON)\***  
Adhesive Thickness


**1.1 MIL (28 MICRON)\***  
Film Thickness

**22 LBS/IN WIDTH\*\***  
Tensile Strength


**110%\*\***  
Elongation % At Break

Test Methods: \* ASTM D-3652; \*\* ASTM D-3759; \*\*\* ASTM D-3330


### AVAILABLE COLORS



### AVAILABLE LENGTHS



### AVAILABLE WIDTHS



### STANDARD FEATURES

- 28 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 22 micron water-based Rohm & Hass acrylic adhesive
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temperature.
- Unlimited Shelf Life
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Available Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets DFA food requirements for indirect food contact.

#### SERVICE TEMPERATURE

Minimum Temp.: **-30°F**  
Maximum Temp.: **200°F**

#### USAGE & STORAGE TEMPERATURE

Minimum Temp.: **32°F**  
Maximum Temp.: **150°F**

#### IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **77°F +/- 5°F**  
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.