



BP22

2.2 MIL (55 MICRON) TOTAL TAPE THICKNESS
30 MICRON CAST BOPP LOW ELONGATION FILM
ROHM & HAAS ACRYLIC ADHESIVE

BP22 is a premium box sealing tape used primarily for heavy duty carton sealing applications. This tape performs well in a broad temperature range.



EXTREME TEMPERATURES



LONG SHELF LIFE



DOESN'T YELLOW TO UV

2.2 MIL (55 MICRON)*
Total Thickness

23 OZ/INCH WIDTH***
Peel Adhesion

1.0 MIL (25 MICRON)*
Adhesive Thickness

1.2 MIL (30 MICRON)*
Film Thickness

24 LBS/IN WIDTH**
Tensile Strength

110%**
Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 30 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 25 micron water-based Rohm & Hass acrylic adhesive
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temperature.
- Unlimited Shelf Life
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Available Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets DFA food requirements for indirect food contact.

SERVICE TEMPERATURE

Minimum Temp.: -30°F
Maximum Temp.: 200°F

USAGE & STORAGE TEMPERATURE

Minimum Temp.: 32°F
Maximum Temp.: 150°F

IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: 77°F +/- 5°F
Ideal Storage Humidity: 55% +/- 5%

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.