



# CSX

#### FULLY AUTOMATIC RANDOM SIDEDRIVE

The BestPack™ CSX Series Fully Automatic Random Carton Sealer's advanced engineering provides the high speed output, and are built for rugged dependability. The CSX design uses three independent operating stations that include the Centering Station, Folding Station, and Sealing Station. For operational dependably and performance, maintenance free oil-less air cylinders are used. These features along with others in our CSX Series set BestPack apart from others in the marketplace. These sealers are designed to meet all your operator free random carton sealing applications.

All BestPack units are available in our standard baked enamel finish or food grade 304 stainless steel for 21 CFR 110 compliance. Custom sizes available for your application.



NO OPERATOR REQUIRED



RANDOM CARTONS



**TOP & BOTTOM SEAL** 

### **110 VOLTS 60 HZ**

Power Requirements

### **UP TO 12 CPM**

Speed


### 100 PSI

Air Requirements

### 1,320 LBS

Shipping Weight

# **CARTON RANGE**



Length (min. - max.) (9.0" - 25.0")

Width (min. - max.) **(6.3" - 20.5")** 

Height (min. - max.) (5.5" - 22.0")

Specifications based on CSX22-2H

## **STANDARD FEATURES**

- Heavy Duty 3mm CNC Cut and Welded Frame Including Upper Welded Legs
- Omron PLC Logic
- Independent Random 3-stage Operation: Centering, Flap Folding, & Sealing
- Random Side Belt Drive with High Speed Motors
- Random Upper Side Compression Rollers
- Interlock Safety Gates
- Capable of Interchanging 2" or 3" BestPack High Speed Tape Heads
- Heavy Duty Maintenance Free Oil-less Air Cylinder Electrical Panel and Air Adjustments are Left Justified (Unless otherwise ordered)

- Tape Roll Lengths: 1,000 yd. & 1,500 yd.
- Low Tape/No Tape on Carton/No Cut Sensors & Alarm with Three Color Warning Light
- UL Approved Electrical Parts
- Heavy Duty Casters
- Low Tape/No Tape on Carton/No Cut Sensors & Alarm with Three Color Warning Light
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

### **OPTIONS**

- Food Grade 304 Stainless Steel
- Retractable Top or Bottom Tape Heads
- Touch Screen Human Interface

- User Specified PLC Brand
- Exit Conveyor

WWW.BESTPACK.COM VERSION 3.1\_0120

# **EXTRA ACCESSORIES TO IMPROVE EFFICIENCY**



#### SPARE PARTS KIT

\*Spare Parts Kits may vary based on machine\* Minimize downtime with BestPack's Spare Parts Kit.



#### **SPARE TAPE HEAD**

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



# LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



#### **FOOD GRADE 304 STAINLESS STEEL**

This machine is available in 304 stainless steel which is food grade safe for food applications.



#### **CARTON SEALING TAPE**

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

# **POPULAR CSX MODELS**

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
CSX22-2H 2" Tape Head	(95.8") x (40.0") x (90.5")	(9.0" - 25.0") x (6.3" - 20.5") x (5.5" - 22.0")	Determined at the time of order	Up to 12	1320
CSX22-3H <b>3" Tape Head</b>	(95.8") × (40.0") × (90.5")	(9.0" - 25.0") × (6.3" - 20.5") × (5.5" - 22.0")	Determined at the time of order	Up to 12	1320

Information subject to change without notice.

\* Outside Dimensions Only All Models Available in Food Grade 304 Stainless Steel

