





HT22

2.2 MIL (56 MICRON) TOTAL TAPE THICKNESS
35 MICRON CAST BOPP LOW ELONGATION FILM
HOT MELT ADHESIVE

HT22 is a heavy duty grade carton sealing tape for those applications needing a strong and sturdy seal.



HIGH SHEAR



GREAT INITIAL TACK



CONSISTENT & EASY RELEASE

2.2 MIL (45 MICRON)*
Total Thickness

.6 KG/CM WIDTH***
Peel Adhesion

0.8 MIL (17 MICRON)*
Adhesive Thickness


1.4 MIL (28 MICRON)*
Film Thickness

4 KG/CM WIDTH**
Tensile Strength


120%**
Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 35 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 21 micron water-based Rohm & Hass acrylic adhesive
- Specially formulated 120% elongation low stretch cast film increasing Machine Length Roll performance.
- Length Roll performance.
- RoHS Compliant
- Tape manufacture in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.
- Available in Hand & Machine Length Rolls

SERVICE TEMPERATURE

Minimum Temp.: **-1°C**
Maximum Temp.: **60°C**

USAGE & STORAGE TEMPERATURE

Minimum Temp.: **0°C**
Maximum Temp.: **40°C**

IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **25°C +/- 21°C**
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.