




MS2B2T COMPARISON CHART

MANUAL SIDRIVE 2 BOTTOM & 2 TOP CARTON SEALER



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

Can't find what your looking for? Customize this model specific to your application. Contact your local BestPack sales representative for more information or inquire at: sales@bestpack.com

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.**	SHIPPING WEIGHT (LBS)
MS2B2T23-2 2" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (10.0" - 21.5") x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435
MS2B2T23-3 3" Tape Head	(39.5") x (36.0") x (68.0")	(6.0" - U) x (10.0" - 21.5") x (5.5" - 30.0")	(20.5" - 30.0")	Up to 40	435

Information subject to change without notice.
 Top Gap Width Range (3.22" - 6.5")
 Bottom Gap Width Range (4.0" - 6.0")

* Outside Dimensions Only
 ** Based on Customer Application
 All Models Available in High Speed & Food Grade 304 Stainless Steel