



MSL


MANUAL SIDEDRIVE LOW PROFILE CARTON SEALER

The BestPack™ MSL is an operator fed, adjustable carton sealer designed to effectively seal very low-profile boxes, in addition to the standard array of carton sizes. The MSL can seal cartons as mere 2.5" high and the upper mast allows for an extra 4" carton height extension on the upper assembly.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



UNIFORM CARTONS



TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power
Requirements

UP TO 40 CPM

Speed


N/A

Air
Requirements

400 LBS

Shipping
Weight

CARTON RANGE



Length (min. - max.)
(6.0" - U)

Width (min. - max.)
(5.7" - 21.0")

Height (min. - max.)
(2.5" - 20.5")

Specifications based on MSL22-2

STANDARD FEATURES

- Side Belt Drive
- Width/Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Seals Cartons as Low as 2.5" in Height
- Upper Side Compression Unit
- Adjustable Bed Height from 20.5" - 30"
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- 3" Model Capable of Interchanging 2" or 3" Tape Heads
- Tape Roll Lengths: 1,000 yd., 1,500 yd., and 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Electrical On/Off Box can be Mounted on Either Side of the Sealer
- Exclusive 2" or 3" Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Locking Heavy-Duty Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- 3-Flap Folder
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



FOOD GRADE 304 STAINLESS STEEL

This machine is available in 304 stainless steel which is food grade safe for food applications.



SPARE PARTS KIT

Spare Parts Kits may vary based on machine
Minimize downtime with BestPack's Spare Parts Kit.



CARTON SEALING TAPE

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR

High Speed Motor Upgrade (up to 125 ft.)

POPULAR MSL MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN. ***	SHIPPING WEIGHT (LBS)
MSL22-2 2" Tape Head	(56.8") x (33.5") x (71.3")	(6.0" - U) x (5.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30")	Up to 40	400
MSL22-3 3" Tape Head	(56.8") x (33.5") x (71.3")	(6.0" - U) x (6.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30")	Up to 40	400

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
*** Based on Customer Application