




RSL COMPARISON CHART

RANDOM SIDEDRIVE LOW PROFILE CARTON SEALER



OPERATOR REQUIRED



RANDOM CARTONS



TOP & BOTTOM SEAL

Can't find what your looking for? Customize this model specific to your application. Contact your local BestPack sales representative for more information or inquire at: sales@bestpack.com

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min. - max.) x WIDTH (min. - max.) x HEIGHT (min. - max.)	CONVEYOR HEIGHT HEIGHT (min. - max.)	CARTONS PER MIN.	SHIPPING WEIGHT (LBS)
RSL22-2 2" Tape Head	(60.4") x (34.8") x (71.8")	(6.0" - U) x (5.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30.0")	Up to 12	450
RSL22-3 3" Tape Head	(60.4") x (34.8") x (71.8")	(6.0" - U) x (6.7" - 21.0") x (2.5" - 20.5")	(20.5" - 30.0")	Up to 12	450

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
All Models Available in High Speed & Food Grade 304 Stainless Steel