

GENERIC & CUSTOM PRINTED TAPE



BestPack's line of custom printed and generic print tape adds security and brand awareness to your packages.

In addition to generic prints that add security to your packages, custom printing capabilities give your packages that professional advertising appeal with your brand name and message.

AVAILABLE TYPES OF PRINT



SAMPLE GENERIC PRINTS



WWW.BESTPACK.COM VERSION 2.3_0320

QUALITY • INNOVATION • COMMUNITY



BESTPACK BG CARTON SEALING TAPE

BestPack's newest product is specially formulated for applications using 100% Recycled Corrugated. By using recycled corrugated (up to 100%), this allows you to not only save money on your packaging costs, but take the next step in improving your overall green footprint.

AVAILABLE GRADES	BG16	BG18	BG20	
Tensile Strength Ibs./in. width	15	15	20	
Elongation %	110	110	110	
Peel Adhesion oz./in. width	16	17	19	
Film Thickness	0.9 mil	0.9 mil	1.0 mil	
Adhesive Thickness	0.7 mil	0.9 mil	1.0 mil	

Usage & Storage Temp. (F): 32° (min.) to 150° (max.)

Service Temp. (F): -30° (min.) to 200° (max.)



WATER-BASED ACRYLIC CARTON SEALING TAPE

BestPack's flagship line of water-based Rohm & Haas acrylic adhesive tape allows for excellent clarity, UV radiation protection against yellowing, usage in extreme temperatures, and long shelf life. Ideal for freezer grade and cold temperature applications, BestPack's acrylic tape is perfect for your food packaging operations.

AVAILABLE GRADES	BP16	BP17	BP18	BP20	BP22	BP26	BP31
Tensile Strength lbs./in. width	20	20	20	22	24	26	31
Elongation %	110	110	110	110	110	140	140
Peel Adhesion oz./in. width	16	17	18	20	23	26.5	27
Film Thickness	1.0 mil	1.0 mil	1.0 mil	1.1 mil	1.2 mil	1.6 mil	2.0 mil
Adhesive Thickness	0.6 mil	0.7 mil	0.8mil	0.9 mil	1.0 mil	1.0 mil	1.0 mil

Usage & Storage Temp. (°F): 32° (min.) to 150° (max.)

Service Temp. (°F): -30° (min.) to 200° (max.)



BESTPACK HOT MELT CARTON SEALING TAPE

Using our unique film structure, consistent release coating, and aggressive synthetic rubber adhesive, the increased tack and sheer will provide a consistent and secure seal for your manual or automated sealing solutions.

AVAILABLE GRADES	HTT16	HT18	HT22	HT25	HT30
Tensile Strength lbs./in. width	19	20	24	26	33
Elongation %	110	110	120	140	140
Peel Adhesion oz./in. width	30	42	51	57	60
Film Thickness	1.0 mil	1.1 mil	1.4 mil	1.6 mil	2.0 mil
Adhesive Thickness	0.6 mil	0.7 mil	0.8 mil	0.9 mil	1.0 mil

Usage & Storage Temp. (°F): 32° (min.) to 104° (max.)

Service Temp. (°F): -30° (min.) to 140° (max.)

*Not All BestPack Tapes are printable



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**