



# AT4E S-FEED STAINLESS

#### **FULLY AUTOMATIC 4-EDGE CARTON SEALER WITH STRAIGHT FEED**

The BestPack AT4E Stainless Steel Series is an operator free, four outer edge carton sealer with corner seals, using pressure sensitive tape. These carton sealers are designed to eliminate costly hand taping of the four outer edges where pilfer proofing and protection of your product from outside environment is necessary. The AT4E Stainless Steel model is designed for uniform edge sealing applications. This unit is designed with an automatic in-line 90 degree box turner.

All BestPack stainless steel sealers are made with food grade 304 stainless steel for 21 CFR 110 compliance and include 304 High Speed stainless steel tape heads. Units are available for either splash resistant or wash-down applications. This unit is also available in standard finish. Standard 3" Tape Head. stainless steel for 21 CFR 110 compliance and include 304 High Speed stainless steel tape heads. Units are available for either splash resistant or wash-down applications. This unit is also available in standard finish. Standard 3" Tape Head.



**NO OPERATOR REQUIRED** 



**UNIFORM CARTONS** 



4-EDGE SEAL

110 V 60 HZ

Power Requirements **UP TO 8 CPM** 


Speed

**80 PSI, 10 SCFM** 

Air Requirements 1,550 - 1,970 LBS

Shipping Weight

### **CARTON RANGE**



Length (min. - max.) (10.3" - 23.5")

Width (min. - max.)

(9.8" - 23.5")

Height (min. - max.) (9.8" - 23.5")

Specifications based on AT4EL22-3S

#### STANDARD FEATURES

- Heavy Duty 3mm Welded 304 Food Grade Stainless Steel Frame Including Upper Welded Legs
- Seals All Four Outside Carton Edges Including All Corners
- In-line 90 Degree Carton Turner
- Four Belt Drive System with 1-piece Molded Belts and V-belt Guide
- Top and Bottom Four 3" Pop-Out BestPack High Speed 304 Stainless Steel Tape Heads
- Low Tape/No Tape on Carton/No Cut Sensors with Malfunction Alarm and Three Color Light

- Motor Drive Uniform Height Adjustment
- Heavy Duty Upper Assembly Four Post System
- Heavy Duty Maintenance Free Oil-less Air Cylinder
- Aluminum Framed Interlock Safety Gates Where Needed
- Tape Roll Lengths: 1,000 yd.
- Quality UL Approved Electrical Parts

### **OPTIONS**

- Spare Parts Kit
- 304 Stainless MSD or 304 Stainless AS-S
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer

WWW.BESTPACK.COM VERSION 4.1\_1020

### **EXTRA ACCESSORIES TO IMPROVE EFFICIENCY**



### 304 STAINLESS STEEL SPARE TAPE HEAD

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



#### SPARE PARTS KIT

\*Spare Parts Kits may vary based on machine\* Minimize downtime with BestPack's Spare Parts Kit.



#### **HIGH SPEED MOTOR**

High Speed Motor Upgrade (up to 125 ft.)



#### **CARTON SEALING TAPE**

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.

## **POPULAR AT4E S-FEED STAINLESS MODELS**

Please refer to comparison chart for complete list of models.

| MODEL                             | MACHINE DIMENSIONS<br>LENGTH x WIDTH x HEIGHT | CARTON RANGE  LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.) | CONVEYOR HEIGHT<br>HEIGHT (min max.) | CARTONS<br>PER MIN. | SHIPPING<br>WEIGHT (LBS) |
|-----------------------------------|---|--|--------------------------------------|---------------------|--------------------------|
| AT4ES22-3S<br><b>3" Tape Head</b> | (110.3") x (49.8") x (60.5")                  | (10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")                      | Determined at the time of order      | Up to 8             | 1,970                    |
|                                   |   | Also Available in L-Feed   |                                      |                     |                          |
| AT4EL22-3<br>3" Tape Head         | (78.9") × (48.5") × (63.0")                   | (10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")                      | Determined at the time of order      | Up to 8             | 1,550                    |

Information subject to change without notice.

