



MTD MANUAL TOP & BOTTOM DRIVE DUAL MAST SEALER

The BestPack[™] MTD Series is a Semi-Automatic Adjustable Tape Carton Sealer, engineered for the economical and effective operator-fed closure of difficult to seal cartons. The MTD Series is four belt drive, to accommodate tall unstable cartons, and comes standard with a manual self-centering mechanism that permits the operator to quickly center the carton and the tape. Dual telescopic masts allow for an extra 4[°] carton height extension on the upper assembly.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



OPERATOR REQUIRED



UNIFORM CARTONS




TOP & BOTTOM SEAL

110 VOLTS 60 HZ

Power Requirements

CARTON RANGE



Length (min. - max.)

(6.0" - U)

Width (min. - max.)

(6.5" - 19.3")

Height (min. - max.)

(4.0" - 20.0") Specifications based on MTD22-2

WWW.BESTPACK.COM

UP TO 40 CPM

Speed

N/A Air Requirements

345-375 LBS Shipping Weiaht

STANDARD FEATURES

- Telescopic Dual Mast Design
- Designed for Uniform Applications
- 4 Belt Drive 2 Top and 2 Bottom Belts
- Adjustable Bed Height from: MTD22 - 23.5" - 30" MTD33 - 25.8" - 30"
- Extra 4" Height Adjustment Available on Upper Assembly
- Height Adjustment Handle can be Mounted on Either Side of the Carton Sealer
- Upper Side Compression Unit
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.

OPTIONS

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Motorized Height Adjustment

- Heavy Duty Frame
- UL Approved Electrical Parts
- Guide Rail Centering Mechanism
- 3" Model Capable of Interchanging 2" or 3" Tape Heads

Infeed/Exit Conveyor w/ L-Bracket Stabilizer

ommunit'

- Interlock Safety Gates
- Low Tape or No Tape Sensor
- Food Grade 304 Stainless Steel

VERSION 4.1_1020

QUALITY •

© 2021 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

EXTRA ACCESSORIES TO IMPROVE EFFICIENCY



LOCKING CASTERS The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



SPARE TAPE HEAD Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 39.5" long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 19.75" short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



FOOD GRADE 304 STAINLESS STEEL This machine is available in 304 stainless steel which is food grade safe for food applications.



SPARE PARTS KIT "Spare Parts Kits may vary based on machine" Minimize downtime with BestPack's Spare Parts Kit.



CARTON SEALING TAPE Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



HIGH SPEED MOTOR High Speed Motor Upgrade (up to 125 ft.)

POPULAR MTD MODELS

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE* LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.***	Shipping Weight (LBS)
MTD22-2 2" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (6.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 40	345
MTD22-2H** 2" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (6.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 50	345
MTD22-3 3" Tape Head	(35.3") x (28.8") x (69.7")	(6.0" - U) x (7.5" - 19.3") x (4.0" - 20.0")	(23.5" - 30.0")	Up to 40	345
MTD22-3H** 3" Tape Head	(35.3") × (28.8") × (69.7")	(6.0" - U) x (7.5" - 19.3") x (4.0"- 20.0")	(23.5" - 30.0")	Up to 50	345
MTD33-3 3" Tape Head	(35.3") x (43.8") x (79.7")	(6.0" - U) x (7.5" - 30.0") x (4.0" - 30.0")	(25.8" - 30.0")	Up to 40	375
MTD33-3H** 3" Tape Head	(35.3") × (43.8") × (79.7")	(6.0" - U) x (7.5" - 30.0") x (4.0" - 30.0")	(25.8" - 30.0")	Up to 50	375

Information subject to change without notice.

U - Unlimited * Outside Dimensions Only ** High Speed *** Based on Customer Application



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**

© 2021 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.