



# RQ

### RANDOM QUAD DRIVE CARTON SEALER

The BestPack™ RQ Series is a Semi-Automatic Random Tape Carton Sealer built for speed and rugged dependability. With a quad-belt drive, the RQ is a heavy-duty work horse that effectively seals unstable cartons, including cartons that are taller than they are long, overfilled, very heavy, or otherwise difficult to seal.

All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



**OPERATOR REQUIRED** 



RANDOM CARTONS



**TOP & BOTTOM SEAL** 

### **110 VOLTS 60 HZ**

Power Requirements

### **UP TO 15 CPM**

Speed


### 90 - 100 PSI, 6 - 8 SCFM

Air Requirements

### 243-333 KG

Shipping Weight

# **CARTON RANGE**



Length (min. - max.) (18 cm. - U)

Width (min. - max.) (19 cm. - 53 cm.)

Height (min. - max.)
(11 cm. - 51 cm.)

Specifications based on RQ22-2

### STANDARD FEATURES

- Adjustable Bed Height from:
   RQ22, RQ23, & RQ33: 52 cm. 76 cm.
   RQ44: 62 cm. 76 cm.
- 4 Belt Drive 2 Top and 2 Side Belts
- Extra 10 cm. Carton Height Adjustment Available on Upper Assembly
- Height Sensor
- Tape Roll Lengths: 914 m., 1,372 m., 1,829 m.
- Heavy Duty Frame
- UL Approved Electrical Parts
- Capable of Interchanging 5 cm. or 8 cm. Tape Heads

- Electrical On/Off Box can be Mounted on Either Side of the Carton Sealer
- Exclusive 5 cm. or 8 cm. Pop-out Pressure Sensitive "High Speed" Tape Head with Patented Tab Adjustment and Noise Reduction Arm

## **OPTIONS**

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 38 m. per min.)
- Heavy-Duty Locking Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Motorized Height and/or Width Adjustment
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

WWW.BESTPACK.COM VERSION 4.1\_1020

# **EXTRA ACCESSORIES TO IMPROVE EFFICIENCY**



#### **LOCKING CASTERS**

The heavy duty locking casters allow the carton sealer quick and easy mobility to other locations.



#### **SPARE TAPE HEAD**

Order a spare tape head with your machine to minimize down time. Having a spare will allow you to drop in a tape head with a new roll of tape in no time!



# SHORT OR LONG INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 50 cm. short or 100 cm. long conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



# SHORT INFEED/EXIT CONVEYOR W/ L-BRACKET STABILIZER

This 50 cm. short conveyor is a great work platform and allows for staging of cartons on the infeed and the exit.



#### SPARE PARTS KIT

\*Spare Parts Kits may vary based on machine\* Minimize downtime with BestPack's Spare Parts Kit.



#### **FOOD GRADE 304 STAINLESS STEEL**

This machine is available in 304 stainless steel which is food grade safe for food applications.



#### **CARTON SEALING TAPE**

Put high quality tape on your BestPack Carton Sealer. Make sure to order machine length rolls for your new carton sealer.



#### **HIGH SPEED MOTOR**

High Speed Motor Upgrade (up to 38 m.)

# **POPULAR RQ MODELS**

Please refer to comparison chart for complete list of models.

MODEL	MACHINE DIMENSIONS LENGTH x WIDTH x HEIGHT	CARTON RANGE*  LENGTH (min max.) x WIDTH (min max.) x HEIGHT (min max.)	CONVEYOR HEIGHT HEIGHT (min max.)	CARTONS PER MIN.	SHIPPING WEIGHT (KG)
RQ22-2 2" Tape Head	(109) x (88) x (146)	(18 - U) x (19 - 53) x (11 - 51)	(52 - 76)	Up to 15	243
RQ22-3 <b>3" Tape Head</b>	(109) x (88) x (146)	(18 - U) x (19 - 53) x (11 - 51)	(52 - 76)	Up to 15	243
RQ23-2 2" Tape Head	(109) x (88) x (193)	(18 - U) x (19 - 53) x (11 - 51)	(52 - 76)	Up to 13	261
RQ23-3 <b>3" Tape Head</b>	(109) x (88) x (193)	(18 - U) x (19 - 53) x (11 - 51)	(52 - 76)	Up to 13	261
RQ EC 33-3 3" Tape Head	(109) x (114) x (193)	(18 - U) x (19 - 76) x (11 - 76)	(52 - 76)	Up to 13	272
RQ33-3-CP** 3" Tape Head	(109) x (114) x (193)	(18 - U) x (19 - 76) x (15 - 76)	(52 - 76)	Up to 13	288
RQ44-3** <b>3" Tape Head</b>	(109) x (139) x (218)	(18 - U) x (19 - 102) x (15 - 102)	(62 - 76)	Up to 12	333

Information subject to change without notice.

U - Unlimited \* Outside Dimensions Only \*\* High Speed

