





HT19

1.83 MIL (46 MICRON) TOTAL TAPE THICKNESS
29 MICRON CAST BOPP LOW ELONGATION FILM
HOT MELT ADHESIVE

HT19 is a general purpose grade hot melt carton sealing tape perfect for light to heavy duty sealing applications.



HIGH SHEAR



GREAT INITIAL TACK



CONSISTENT & EASY RELEASE

1.83 MIL (46 MICRON)*
Total Thickness

47 OZ/INCH WIDTH***
Peel Adhesion

0.67 MIL (17 MICRON)*
Adhesive Thickness


1.16 MIL (29 MICRON)*
Film Thickness

26 LBS/IN WIDTH**
Tensile Strength


165%**
Elongation % At Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330


AVAILABLE COLORS



AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 29 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 17 micron hot melt adhesive
- Specially formulated 165% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufacture in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.
- Available in Hand & Machine Length Rolls

SERVICE TEMPERATURE

Minimum Temp.: **30°F**
Maximum Temp.: **140°F**

USAGE & STORAGE TEMPERATURE

Minimum Temp.: **50°F**
Maximum Temp.: **110°F**

IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **40°F +/- 5°F**
Ideal Storage Humidity: **40% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.