


EZ-PEEL TAPE

MADE WITH ROHM & HAAS ACRYLIC ADHESIVE

EZ-Peel Tape is a new innovation that has deadened adhesive on the edge of the film for easy removal of tape. No more accidental cuts and/or punctures into product. EZ-peel provides the quality seal you're looking for and prevents damage on products. Available in both hand and machine rolls



NO BLADE NEEDED



CUSTOM PRINTING AVAILABLE



ENVIRONMENTALLY FRIENDLY

NO CUTTING NEEDED

Protection for your products

AVAILABLE

Custom Brand Print

YES

Environmentally Friendly

1.6 MIL (40 MICRON)*
Total Thickness

16 OZ/INCH WIDTH***
Peel Adhesion

0.6 MIL (15 MICRON)*
Adhesive Thickness


1.0 MIL (25 MICRON)*
Film Thickness

20 LBS/IN WIDTH**
Tensile Strength


110%**
Elongation % at Break

Test Methods: * ASTM D-3652; ** ASTM D-3759; *** ASTM D-3330

AVAILABLE LENGTHS



AVAILABLE WIDTHS



STANDARD FEATURES

- 25 micron cast biaxially oriented polypropylene (BOPP) low elongation film
- 15 micron water-based Rohm & Haas acrylic adhesive
- Specially formulated Rohm & Haas acrylic adhesive for use in Hot & Cold Temperature.
- Unlimited Shelf Life
- Does not yellow due to UV exposure (sunlight & fluorescent lighting)
- Available Hand & Machine Length Rolls
- Specially formulated 110% elongation low stretch cast film increasing Machine Length Roll performance.
- RoHS Compliant
- Tape manufactured in ISO 9001 & 14001 Facilities
- Meets FDA food requirements for indirect food contact.

SERVICE TEMPERATURE

Minimum Temp.: **-30°F**
Maximum Temp.: **200°F**

USAGE & STORAGE TEMPERATURE

Minimum Temp.: **32°F**
Maximum Temp.: **150°F**

IDEAL STORAGE TEMPERATURE

Ideal Storage Temp.: **77°F +/- 5°F**
Ideal Storage Humidity: **55% +/- 5%**

Values obtained from tests do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. BestPack recommends the user to determine whether the product is fit for a particular purpose and is suitable for the user's method of application.