

# C-SERIES CARTON SEALER APPLICATION FORM

## END USER INFORMATION

Company Name

Address

City  State  Zip Code

Contact Name & Title

Telephone No.

E-Mail

## DISTRIBUTOR INFORMATION

Company Name


Address

City  State  Zip Code

Contact Name & Title

Telephone No.

E-Mail



| LENGTH               | WIDTH                | HEIGHT               | WEIGHT               | % OF PRODUCTION      |
|----------------------|----------------------|----------------------|----------------------|----------------------|
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |
| <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> |

**CARTON STATUS**

Filled

Underfilled

Overfilled

Re-Used

**SAMPLE CARTONS SENT**

Yes  No

## CARTON INFORMATION

### CARTONS

RSC

HSC

Other

### CARTON TO BE TAPED:

Top & Bottom  Bypass Needed

Top Only

Bottom Only

4-Edge Seal

### TAPE:

2" (48mm)

3" (72mm)

4" (96mm)

6" (144mm)

Packing Room Temperature:

### PACKING ROOM CONDITIONS:

Normal  Wet  Dusty  Corrosive

## POWER REQUIREMENTS

### FLOW DIRECTION STANDING IN FRONT OF ELECTRICAL BOX:

Right to Left (Standard)

Left to Right

### ELECTRICAL REQUIREMENTS

110v 1-Phase  208v 3-Phase

240v 1-Phase  480v 3-Phase

## AIR REQUIREMENTS

### IS THERE AN AIR DRYER?

Yes

No

PSI:

SCFM:

## CARTONS PER

Minute:  Shift:

Hour:  Day:

### RECOMMENDED MODEL:

### CONVEYOR HEIGHT

Conveyor Height:

Infeed Conveyor Powered

Exit Conveyor Powered

# FACILITY INFORMATION

## ARE THESE MACHINES GOING INTO A NEW OR EXISTING FACILITY?

### FACILITY TECHNICAL SUPPORT:

|   |   |                                    |                      |
|---|---|------------------------------------|----------------------|
| <input type="text"/>                      | <input type="text"/>                      | <input type="text"/>               | <input type="text"/> |
| Number of Techs with Mechanical Knowledge | Number of Techs with Electrical Knowledge | Number of Techs with PLC Knowledge | Number of Engineers  |

### CAN PRODUCTION ACCOMMODATE DOWN TIME FOR TAPE ROLL CHANGES?

Yes  No

### CAN PRODUCTION ACCOMMODATE DOWN TIME FOR MAINTENANCE?

Yes  No

For fully automatic applications it is the responsibility of the end user to inform their corrugator that the cartons need to be well scored, with proper glue joints, and 3/8" or larger slots. Applications for CSX type fully automatic random sealers require minor flaps to be slightly tucked inside major flaps before closing.

Comments

Completed By

Date

**PLEASE EMAIL COMPLETED FORM TO SALES@BESTPACK.COM**



For more information please go to:  
**WWW.BESTPACK.COM** or call us at **1.888.588.2378**