



*Model Shown: PP-5600CS

5600 SERIES

FULLY AUTOMATIC L-BAR SEALER

Ideal for sealing a wide variety of industrial and consumer products


PRODUCTION
RATE:
up to 40 ppm

MAX FILM
WIDTH:
(24.0")

MACHINE DIMENSIONS:
(L X W)
(77.0" x 62.0" x 72.0")

SEAL DIMENSIONS:
(L X W X H)
(25.0" x 15.0" x 8.0")

Specifications based on PP-5600CS



Our fully automatic L-Bar Sealer is the only automated L-Sealers and Tunnels to feature “APA” Automatic Product Adjustment. The operator simply selects the desired program from the one-touch control panel and the machine will automatically adjust the infeed conveyor and inverting triangle to package size in less than 15 seconds. No more fussing with crank handles or guessing the proper package size.

AVAILABLE MODELS:

- PP-5600-CS
- PP-5600-CC
- PP-5600-CS-COMBO
- PP-5600-CC-COMBO

FULLY AUTOMATIC L-BAR SEALERS

STANDARD FEATURES INCLUDE:

- “APA” Automatic Product Adjustment
- Vertical Seal Head Design with Center Seal
- Delta 7” Color Touch Screen with 40 Program Memory
- Variable Speed Drive 0-110 FPM
- Delta PLC
- Self-Diagnostics
- Multi-pack option
- Product Staging
- Motorized Scrap Wind up with Alarm
- Pinwheel Hole Punch
- Single Piece Hot Knife Seal Bar
- Locking Casters
- 220V, 1 Phase, 20A
- Max Film Width 24”

OPTIONS:

- Closing Conveyor
- Print Film Registration
- Left to Right Product Flow
- Export Crating
- Non-Standard Voltage
- Pneumatic Hole Punch Single Hole 3/16”
- Dual Pneumatic Hole Punch (Two 3/16” Diameter Holes)
- Poly cord belt infeed conveyor (For easy cleaning)
- 10” Color Touch Screen HMI
- Pressure Roller to Help Move Light Products
- PP-36B 3ft Belted infeed conveyor
- PP-72B 6ft Belted infeed conveyor
- PP-36F 3ft Flighted infeed conveyor
- PP-72F 6ft Flighted infeed conveyor
- PP-72FB 6ft Flighted “Bar” Style Infeed Conveyor (Pushes multiple products at the same time)
- Pneumatic Product Hold Down for Light Weight Products
- Pneumatic Air Expeller Helps Evacuate Air from Bag Prior to Sealing
- Short Stroke Cylinder on Seal Head for Increased Speeds of Up to 50 PPM

POPULAR FULLY AUTOMATIC L-BAR SEALER MODELS

MODELS	SEALING AREA (LENGTH X WIDTH X HEIGHT)	MIN PACKAGING SIZE (LENGTH X WIDTH X HEIGHT)	MAX PACKAGING SIZE (LENGTH X WIDTH X HEIGHT)	PACKAGES PRE MINUTE
PP-5600-CS	(25.0" x 15.0" x 8.0")	(2.5" x 2.5" x 0.125")	(24.0" x 16.0" x 8.0")	up to 40
PP-5600-CC				
COMBO MODELS	SEALING AREA (LENGTH X WIDTH X HEIGHT)	MIN PACKAGING SIZE (LENGTH X WIDTH X HEIGHT)	MAX PACKAGING SIZE (LENGTH X WIDTH X HEIGHT)	PACKAGES PRE MINUTE
PP-5600-CS-COMBO	(25.0" x 15.0" x 8.0")	(2.5" x 2.5" x 0.125")	(24.0" x 16.0" x 8.0")	up to 40
PP-5600-CC-COMBO				

Information subject to change without notice.

CC-Closing Conveyor