



*Model Shown: PP-1808-28

18" SERIES

MEDIUM CAPACITY HEAT SHRINK TUNNELS


Can be used with a wide variety of applications

PRODUCTION
RATE:
up to 75 FPM

POWER
REQUIREMENTS
220 VOLT 1 PHASE 40 AMPS

CHAMBER DIMENSIONS:
(L X W X H)
(28.0" x 18.0" x 8.0")

WEIGHT
(450 lbs)



Specifications based on PP-1808-28

The PP-1808-28 Shrink Tunnel is a great general-purpose shrink tunnel that can be used for a wide variety of applications. Can be used with shrink bands, neck bands, full body sleeves, used with shrink film, used as drying or curing tunnel etc.

AVAILABLE MODELS:

- PP-1808-28
- PP-1812-28
- PP-1808-44
- PP-1812-44

HEAT SHRINK TUNNELS

STANDARD FEATURES INCLUDE:

- Fully Re-Circulating Air Chamber
- Live Roller Rod Conveyor
- Digital Temperature Control 0-400°
- Adjustable Air Velocity Control
- AC Variable Speed Drive 0-75 FPM
- Automatic Cool Down with Shut Off
- Locking Casters with Leveling Pads
- 12 ft Power Cord
- Anti-Jam Safety Features on Conveyor

GENERAL PURPOSE FEATURES:

- 1/2 HP Blower Motor
- 7.5 KW Heater Bank

MEDIUM CAPACITY FEATURES:

- 1HP Blower Motor
- 9 KW Heater Bank

OPTIONS:

- Increase Tunnel Height 4" increments (28" max)
- Non-standard voltage
- Paint – Custom colors
- High density roller kit
Rollers on 1" centers, ½" spacing
- Teflon mesh belt overlay kit
- Stainless steel metal mesh belting
- Heavy duty plastic falcon belting
- Export crating
- Infeed or discharge extensions (per ft)
- Side guide rails in tunnel
- Convert to dead roller conveyor
(for shrinking Polyethylene Films)

POPULAR HEAT SHRINK TUNNEL MODELS

GENERAL MODELS	CHAMBER SIZE (LENGTH X WIDTH X HEIGHT)	MACHINE DIMENSIONS (LENGTH X WIDTH X HEIGHT)	POWER REQUIREMENTS	WEIGHT
PP-1808-28	(28.0" x 18.0" x 8.0")	(40.0" x 26.0" x 61.0")	220 Volts 40 AMPS 1 Phase	450 lbs
PP-1812-28	(28.0" x 18.0" x 12.0")			500 lbs
MEDIUM MODELS	CHAMBER SIZE (LENGTH X WIDTH X HEIGHT)	MACHINE DIMENSIONS (LENGTH X WIDTH X HEIGHT)	POWER REQUIREMENTS	WEIGHT
PP-1808-44	(44.0" x 18.0" x 8.0")	(61.0" x 26.0" x 61.0")	220 Volts 40 AMPS 1 Phase	675 lbs
PP-1812-44	(44.0" x 18.0" x 12.0")			500 lbs

Information subject to change without notice.