



BESTPACK
BPX SOLUTIONS



*Model Shown: PP-5545TBH

5545 SERIES

AUTOMATIC SIDE SEALER


Intermittent Motion Side-Sealer

PRODUCTION
RATE:
up to 60 ppm

MAX FILM
WIDTH:
(25.0")

MACHINE DIMENSIONS:
(L X W)
(82.7" x 58.3.0" x 51.5")

SEAL DIMENSIONS:
(L X W)
(18.0" x 6.0")



Specifications based on PP-5545TBH

Meet the high-speed side sealing solution that will automate your packing for long products. This solution was built with an intermittent sealing motion with for both speed and economy. Equipped with a sturdy HMI providing the operator with easy to read and adjust operational parameters. The automatic side sealer is equipped with a servo motor allowing for a high-speed design with a sealing capacity of up to 60 packages per minute. The side sealing machine is also equipped with a one-piece, Teflon coated, heat-resistant alloy blade.

AVAILABLE MODELS:

- PP-5545TBH
- PP-5545TBJ-F
- PP-5545TBJ-B

AUTOMATIC SIDE SEALERS

STANDARD FEATURES INCLUDE

- Omron PLC
- Teflon Coated Hot Knife Cross Seal Bar
- Servo Motor Drive on Cross Seal
- Independent Digital Temperature Controls
- Omron Color Touch Screen
- Motorized Scrap Wind Up Wheel with Built In Alarm When Full
- Emergency Stop Switch with Reset Button
- Automatic Pin Wheel Hole Punch
- Powered In-Feed Conveyor with Electric Eye to Start Cycle
- Adjustments for Bag Size Front And Back
- Rear Mounted Film Carriage
- Accepts Random Length Products, No Changeover Required
- Adjustable Height Legs with Locking Casters
- Fully Enclosed Seal Area
- Safety Interlocks on All Doors
- Air Required 3-4 CFM at 80 PSI
- Omron Inverter Drives With Variable Speed Drive 0 To 100 FPM

OPTIONS:

- Closing Conveyor to Transfer Small Package Sizes

POPULAR AUTOMATIC SIDE SEALER MODELS

MODELS	SEALING DIMENSIONS CROSS SEAL x HEIGHT		POWER REQUIREMENTS	MAX PACKAGE SIZE WIDTH x HEIGHT	MAX FILM WIDTH	PACKAGES PRE MINUTE	
PP-5545TBH	(18.0" x 6.0")		220V, 1 Phase, 15A	(15.0" x 6.0")	(25.0")	up to 60	

MODELS	INFEED TYPE	SEALING DIMENSIONS CROSS SEAL x HEIGHT	POWER REQUIREMENTS	PACKAGE LENGTH	PACKAGE WIDTH	MAX FILM WIDTH	PACKAGES PRE MINUTE
PP-5545TBJ-F	Flighted	(17.7" x 6.0")	220V, 1 Phase, 15A	(2.5" x U")	(3.0" x 16.0")	(25.0")	up to 75
PP-5545TBJ-B	Belted	(17.7" x 6.0")	220V, 1 Phase, 15A	(2.5" x U")	(3.0" x 16.0")	(25.0")	up to 75

Information subject to change without notice.

U - Unlimited