

	LER APPLICAT	ION FORM	1	DEAL ID			
Company Name	ND USER INFORMATION	Cor	mpany Name	DISTRIBUTOR INFORM	MATION		
Address		Ado	dress				
City	State Zip Code	City	,	State	Zip Code		
Contact Name & Title		Cor	ntact Name & Title				
Telephone No.		Tele	ephone No.				
E-Mail		E-M	1ail				
H	LENGTH WIDTH	HEIGHT	WEIGHT	% OF PRODUCTION	CARTON STATUS Filled Underfilled Overfilled Re-Used		
W					SAMPLE CARTONS SENT Yes No		
CARTON INFORMATION							
RSC To	N TO BE TAPED: op & Bottom	TAPE: 2 " (48r 3 " (72r	(0011111	n) Normal nm)	RROOM CONDITIONS: Wet Dusty Corrosive m Temperature:		
ARE YOU RUNNING: In Batches Rar	SHOULD THE I	MACHINE CLOSE: Bottom Flap		IERE BE AN OPERATOR	R TO FEED THE MACHINE?		
POWER REQUIREMENTS FLOW DIRECTION STANDING IN FRONT OF ELECTRICAL BOX: Right to Left (Standard) Left to Right POWER REQUIREMENTS 110v 1-Phase 208v 3-Phase 220v 1-Phase 480v 3-Phase			AIR REQUIREMENTS CARTONS PER Minute: Shift: Yes SCFM: Hour: Day:		Shift:		
RECOMMENDED MODEL:			CONVEYOR Conveyor Height		d Conveyor Powered Conveyor Powered		

WWW.BESTPACK.COM VERSION 1.7_0224

FACILITY INFORMATION

ARE THESE MACHINES GOING INTO A NEW OR EXISTING FACILITY?

FACILITY TECHNICAL SUPPORT:

Number of Techs with Mechanical Knowledge

Number of Techs with Electrical Knowledge Number of Techs with PLC Knowledge

Number of Engineers

CAN PRODUCTION ACCOMMODATE DOWN TIME FOR TAPE ROLL CHANGES?

Yes

No

CAN PRODUCTION ACCOMMODATE DOWN TIME FOR MAINTENANCE?

Yes

No

For fully automatic applications it is the responsibility of the end user to inform their corrugator that the cartons need to be well scored, with proper glue joints, and 3/8" or larger slots. Applications for C-Series type fully automatic random sealers require minor flaps to be slightly tucked inside major flaps before closing.

Comments		
	Completed By	Date

PLEASE EMAIL COMPLETED FORM TO SALES@BESTPACK.COM



For more information please go to: **WWW.BESTPACK.COM** or call us at **1.888.588.2378**